

### Executive Engineer B&R Division HP.PWD. Joginder Nagar

Himachal Pradesh Public Works Department, Mandi-175015 Phone & Fax No. 01908-222033 E-Mail:- ee-jog-hp@nic.in

### "NOTICE INVITING TENDER"

Sealed item rate tender for the following works are hereby invited by the Executive Engineer, B&R Division HP.PWD., Joginder Nagar District Mandi (H.P) from the eligible contractors of the appropriate class registered in HP.PWD. as per revised enlistment rules so as to reach in the office of under signed on 25/06/2022 up to 11:30 A.M. and will be opened on the same day at (12:00 noon) in the presence of intending contractors. The tender application will be received in this office against cash payment on 23/06/2022 up to 10.00 A.M. to 12:30 P.M. and tender form can be had from this office on 24/06/2022 from 2.00 P.M. to 5.00 Pm. The earnest money as shown against each in the shape of F.D.R of any bank in Himachal Pradesh duly pledged in the name of the under signed must accompany with each tender. The tender form will be issued to contractor giving proof of enlistment, GST, work done certificate, proof of machinery etc. Conditional tender and tender received without earnest money will be out rightly rejected. The offer of the tender shall be kept open for 90 days. The Executive Engineer reserves the right to reject any or all the tenders without assigning any reasons.

The draft NIT and other specifications and conditions of the tender can be seen by the contractors in the office of the under signed on any working day during the office hours

| Sr.<br>No. | Name of work   | Amount put to tender/ Est. cost | Earnest money | Cost of<br>Tender<br>Form | Eligible<br>Class of<br>Contractor | Time            |
|------------|--|---------------------------------|---------------|---------------------------|------------------------------------|-----------------|
| 1          | Construction of link road from Kas to Patolu Km. 2/0 to 5/0. (Sub Head:- Construction of U-Shape drain/ Kuhal at Km. 3/420).   | ₹ 72,316/-                      | ₹ 1,400/-     | ₹ 350/-                   | Class "D"                          | Three months    |
| 2          | Improvement of Joginder Nagar Sarkaghat<br>Ghumarwin road Km. 0/0 to 21/500. (Sub<br>Head:- Construction of retaining wall at Km.<br>1/700 to 1/710).  | ₹ 1,77,193/-                    | ₹ 3,500/-     | ₹ 350/-                   | Class "D"                          | Three           |
| 3          | Improvement of road geometrics on Joginder Nagar Sarkaghat Ghumarwin road Km. 0/0 to 21/500. (Sub Head:-Construction of retaining wall at Km. 18/562.50 to 18/570).  | ₹ 4,19,132/-                    | ₹ 8,4000/-    | ₹ 350/-                   | Class "D"                          | Three months    |
| 4          | Construction of Joginder Nagar Arthi road<br>to join with Syuri Majharnu road &<br>construction of bridge over Neri Khad. (Sub<br>Head:- Construction of wire crate retaining<br>wall at Km. 1/015 to 1/059) | ₹ 4,91,450/-                    | ₹ 9,800/-     | ₹ 350/-                   | Class "D"                          | Three months    |
| 5          | A/R & M/O link road to village Sainthal<br>Bhala ka Rihra Tikru Km.0/0 to 9/0. (Sub<br>Head:- Construction of breast wall at Km.<br>1/960 to 1/985 & Km. 2/290 to 28/302).                                   | ₹ 3,79,219/-                    | ₹ 7,600/-     | ₹ 350/-                   | Class "D"                          | Three<br>months |

### Certified that tender of above works are being called of emergent nature in exigency of public interest

### Terms and conditions:-

- 1 The contractor should produce a copy of enlistment / renewal letter at time of application.
- 2 Executive Engineer reserves the right to reject/cancel any or all the tenders without assigning any reasons.
- The contractor/Firm shall have his registration and GST No, the copy of same be attached with the application. 3.
- 4. The earnest money shall be deposited duly pledged in favour of Executive Engineer B&R Division HPPWD., Joginder Nagar & cost of tender form for the above works should be submitted with the application for the purchase of the tender forms. The application received without earnest money & cost of tender form shall summarily be rejected.
- 5 No tender form will be issued to the contractor without producing the work done certificate from the Executive Engineer concerned.
- 6 The Contractor/Firms must have executed minimum one civil /similar nature of work done of amount not less than 40% (forty percent) of the estimated cost (without Liquidated Damage or compensation) in last five years.
- The contractor/firms are requested to insert the rate of each item in words as well as in figures failing which XEN reserves the right to 7 accept/reject any tender without assigning any reason at any stage.
- 8 The tender shall be issued to those contractors who have not more than two works in hand.

**Executive Engineer, B&R Division HP PWD...** Joginder Nagar. District Mandi (HP) on behalf of

16-6-2022

Governor of Himachal Pradesh Ph. 01908-222033

Dated:-

No. PW-JND-B&R-EA-I/NIT/Press/2022-23- 800 -34

Copy to the F.C. Cum Principal Secretary (PW) to the Govt. of Himachal Pradesh Shimla-2 for favour of information please.

The Engineer-in-Chief, HPPWD, Shimla.

The Chief Engineer (MZ), HPPWD, Mandi.

The Superintending Engineer, Joginder Nagar Circle HPPWD, Joginder Nagar.

All the Executive Engineer in HPPWD for wide publicity.

6. All the Assistant Engineer working under this Division.

Drawing Branch in this office.

Notice Board.

The Computer Cell office of the Engineer-in-Chief, HPPWD, Shimla for uploading the NIT on the Departmental website.

Executive Engineer, RAR Division HP PWD Jeginder Nagar.

|                                  |   |                    |        | Total  |             |
|----------------------------------|---|--------------------|--------|--|-------------|
|                                  |   | Per<br>Kilogramme  | 354.38 | Supplying, fitting and placing HYSD bar reinforcement in sub structure complete as per drawing and technical specifications clauses 1002, 1010 and 1202 complete within all leads, lifts carriage of material and other incidentials.  | 5           |
|                                  |   | Per cubic<br>metre | 3.75   | Providing and laying reinforced cement concrete in sub structure as per drawing and technical specifications clauses 800, 1205.4 & 1205.5. Reinforced cement concrete M-25 (1:1.5:3) (one cement conc and half sand: three graded stone aggregate 20mm (twenty millimetre) nominal size) upto any height complete within all leads, lifts carriage of material and other incidentials.   | ω           |
|                                  |   | metre              |        | specification section 300 & 1600 including setting out, construction of shoring and bracing, removal of stumps and other deleterious materials and disposal in all lead and lift including dressing of sides and bottom and back filling in trenches with excavated Suitable materials. All work of rock cutting by blasting shall be carried out by taking all necessary precautions against soil erosion, damage to hill side, water pollution etc. and to protect stability of hill side rock shall be excavated with chiseling and wedging out rock (where blasting is prohibited). All earth work in cutting/excavation including rock excavation shall be carried out true to lines grades, side slopes, width, camber super elevation and level as shown on the drawings or as directed by the Engineer-in-Charge, hauling and stacking of materials useful for construction at suitable sites and safe disposal of unsuitable cut materials in specified manner, filling of unevenness and finishing the road to specified dimension or as directed by the Engineer-in-Charge. If the foundation of the structure is in an area with stagnant water or water is met with in the excavation due to spring seepage, rain and other causes it shall be removed by suitable diversion, bailing out or pumping as directed and the area of the foundation or embankment shall be kept dry. Any loss to the public or private property during the course of excavation shall be the whole responsibility of the contractor which shall have to be duly compensated by him at his own cost. |             |
| Rs. P                            | Figures Words                             | Deronkin           | Qty.   | Earth work in averagation for etructures in all deaths as  | No.         |
| AMOUNT                           | Rate                                      | Unit               | No. or | Description of work  | Sr.         |
| 72,316.0<br>1,400.0<br>Two Month | Estimate Cost: Earnest Money: Time Limit: |                    |        | Name of Work: Construction of Link road from Kas to Patholu km 2/00 to 5/00. (S.H.: Construction of U-Shape Drain/Kuhl Crossing at Km 3/420)   | Nan<br>(S.H |
|                                  | (   |                    |        |  | 1           |

Exceptive Engineer

B & R Division HP.PWD,

Joginder Nagar

| - |   |    |
|---|---|----|
|   | - | 0  |
| 1 | N | 10 |
| 1 |   | 1  |
|   | 1 |    |

(SH: Construction of Retaining wall at km 1/700 to 1/710) Name of Work: Improvement and widening of Joginder Nagar Sarkaghat Ghumarwin Road km 0/00 to 7/200 Earnest Money: Time Limit: **Estimate Cost:** 3,500. Three Mont 1,77,193.

| Description of work  Providing weep holes in brick masonry/stone masonry/plain or reinforced concrete abutme wing wall, return wall with 100mm (one hundred millimeter) dia P.V.C. pipe extending throu | No. or Oty. ain or reinforced concrete abutment, 8.00 er) dia P.V.C. pipe extending through | No. or Unit Oty. 8.00 Each  | No. or Unit Figures  8.00 Each | No. or Unit Oty.  8.00 Each   |
|---|---|-----------------------------|--------------------------------|-------------------------------|
|   | No. or<br>Oty.<br>8.00  | No. or Unit Oty.  8.00 Each | No. or Unit Figures 8.00 Each  | No. or Unit Figures 8.00 Each |
|   |   |                             | Figures                        | Figures                       |

Executive Engineer
B & R Division HP.PWD,
Jogander Nagar

| Name 21/500 (SH: C Sr. No. 1 Eas specific Specif | 1 Ea spi dra wc wi in- sol dis str see see while while while with the see see while while with the see see while with the see see while with the see see see while with the see see see see see with the see see see see see see see see see s   | 2 Prosto   |
|--|--|--|
| Name of Work: Improvement of Road Geometrics on Joginder Nagar Sarkaghat Ghumarwin Road Km 0/00 to 21/500  (SH: Construction of Retaining wall at km 18/562.50 to 18/570)  Sr. Description of work  No. Description of work  1 Earth work in excavation for structures in all depths as per drawing and M.O.R.D.technical 27.56 Per cu specification section 300 & 1600 including setting out, construction of shoring and bracing, metu   | Earth work in excavation for structures in all depths as per drawing and M.O.R.D.technical specification section 300 & 1600 including setting out, construction of shoring and bracing, removal of stumps and other deleterious materials and disposal in all lead and lift including dressing of sides and bottom and back filling in trenches with excavated Suitable materials. All work of rock cutting by blasting shall be carried out by taking all necessary precautions against soil erosion, damage to hill side, water pollution etc. and to protect stability of hill side rock shall be excavated with chiseling and wedging out rock (where blasting is prohibited). All earth work in cutting/excavation including rock excavation shall be carried out true to lines grades, side slopes, width, camber super elevation and level as shown on the drawings or as directed by the Engineer-in-Charge, hauling and stacking of materials useful for construction at suitable sites and safe disposal of unsuitable cut materials in specified manner, filling of unevenness and finishing the road to specified dimension or as directed by the Enginer-in-Charge. If the foundation of the structure is in an area with stagnant water or water is met with in the excavation due to spring seepage, rain and other causes it shall be removed by suitable diversion, bailing out or pumping as directed and the area of the foundation or embankment shall be kept dry. Any loss to the public or private property during the course of excavation shall be the whole responsibility of the contractor which shall have to be duly compensated by him at his own cost. | Providing and laying cement concrete 1:5:10(one cement: five sand:ten graded crushed / broken stone aggregate 40 mm (forty milimeters) nominal size) plums and curing complete including the cost of form work in <b>Retaining walls Breast walls</b> , in or under water complete including, pumping or bailing out water ,dewatering removal of slush as required at site which may arisen at the time of laying under water complete for all heights/depths including cost of form work as per drawings and MORD technical specifications section 800, 900,1200 & 1600 and as per the direction of Engineer-in-Charge including carriage of material within all leads and lifes and other direction of Engineer-in-Charge including carriage of material within all leads and lifes and other |
| Road Kn  No. or  Oty.  27.56   | 27.56  | 71.25  |
| Unit  Per cubic metre  |  | Per cubic<br>metre   |
| Figures  |  |  |
| Estimate Cost: Earnest Money: Time Limit: Rate Words   |  |  |
| 4,19,132.<br>8,400.<br>Three Mont<br>AMOUNT<br>Rs. P   |  |  |

|       |  |   | 20                    |
|-------|--|---|-----------------------|
|       | 4<br>7 2 2 2 0 H   | 3 E   | No.                   |
| Total | Providing weep holes in brick masonry/stone masonry/plain or reinforced concrete abutment, wing wall, return wall with 100mm (one hundred millimeter) dia P.V.C. pipe extending through the full width of the structures with slope of I (v): 20(H) towards drainage face complete as per drawing and M.O.R.D.technical specification clauses 614, 709 & 1206.6 and as per the directions of Engineer-in-Charge including carriage of material within all leads and lifts and other incidentals and to the entire satisfaction of the Engineer-in-Charge . | 3 Back filling behind abutment wing wall and return wall complete as per Drawing and technical specifications clause 1204.3.8 Granular material complete within all leads, lifts carriage of material and other incidentials. | Description of work   |
|       | 24.00  | 17.55   | No. or<br>Qty.        |
|       | Each   | 17.55 Per cubic metre   | Unit                  |
|       |  | 5   | Figures               |
|       |  |   | Rate<br>Figures Words |
|       |  |   | AMOUNT<br>Rs. P       |

Executive Engineer

B & R Division HP.PWD,

Joginder Nagar

| 1   |   |         |                    | 0 -     |                       |             |
|-----|---|---------|--------------------|---------|-----------------------|-------------|
| BN  | Name of Work:- Construction of Joginder Nagar Arthi road to join with Syuri Majharnoo raod & C/O bridge over  | 1 & C/O | bridge over        | (       | <b>Estimate Cost:</b> | 4,91,450.0  |
| Zei | Neri Khad. (SH: Construction of Wire Carte Retaining wall at km 1/6/5 to 1/059)   |         |                    | -       | Earnest Money:        | 9,800.0     |
|     |   |         |                    |         | Time Limit:           | Three Montl |
| Sr. | Description of work   | No. or  | Unit               | I       | Rate                  | AMOUNT      |
| - 1 | Farth work in expansion for etructures in all deaths as nor describe and MOD Death in the in-   | VIV.    |                    | rigures | Words                 | Rs. P       |
| -   | 300 & 1600 including setting out, construction of shoring and bracing, removal of stumps and other deleterious  | 36.30   | Per cubic<br>metre |         |                       |             |
|     | excavated Suitable materials. All work of rock cutting by blasting shall be carried out by taking all necessary precautions against soil erosion, damage to hill side, water pollution etc. and to protect stability of hill side rock  |         |                    |         |                       |             |
|     | shall be excavated with chiseling and wedging out rock (where blasting is prohibited). All earth work in cutting/excavation including rock excavation shall be carried out true to lines grades, side slopes, width, camber super elevation and level as shown on the drawings or as directed by the Engineer in Charge builties and attacking super elevation and level as shown on the drawings or as directed by the Engineer in Charge builties and attacking   |         |                    |         |                       |             |
|     | of materials useful for construction at suitable sites and safe disposal of unsuitable cut materials in specified manner, filling of unevenness and finishing the road to specified dimension or as directed by the Enginer-in-   |         |                    |         |                       |             |
|     | Charge. If the foundation of the structure is in an area with stagnant water or water is met with in the excavation due to spring seepage, rain and other causes it shall be removed by suitable diversion, bailing out or  |         |                    |         |                       |             |
|     | pumping as directed and the area of the foundation or embankment shall be kept dry. Any loss to the public or private property during the course of excavation shall be the whole responsibility of the contractor which shall  |         |                    |         |                       |             |
|     | have to be duly compensated by him at his own cost.   |         |                    |         |                       |             |
| 12  | Providing and laying of boulder apron laid in wire crates with 4mm (four millimetre) diametre G.I. wire conforming to IS: 280 and IS: 4826 in 100mm x 100mm (one hundred millimetre into one hundred millimetre)  | 137.50  | Per Cubic          |         |                       |             |
|     | mesh (woven diagonally) including 10% (ten percent) extra for laps and joints laid with stones boulders weighting not less than 25 Kg (twenty five kilogram) each as not drawing and technical accordance land to the land to |         | mene               |         |                       |             |
|     | within all leads, lifts, carriage of material and other incidentials.   |         |                    |         |                       |             |
| w   | Back filling behind abutment wing wall and return wall complete as per Drawing and technical specifications clause 1204.3.8 Granular material complete within all leads, lifts carriage of material and other incidentials.   | 26.40   | Per cubic<br>metre |         |                       |             |
|     |   |         |                    |         |                       |             |
| Γ   | Total   |         |                    |         |                       |             |

Executive Engineer

B & R Division HP.PWD,

Joginder Nagar

| Description of work | SHOIL OF DECASE WAIT AT KIT 1/900 to 1/985 & 2/290 to 2/202) | k: A/R & M/O Link road to Village Sainthal Bhala ka Rihra Tikru km 0/00 to 9/00 | CHECKLE OF COUNTIL |
|---------------------|--|---|--------------------|
| No. or              |  | 00  | 1                  |
| Unit                |  |   |                    |
| Rate                | Earnest Money:<br>Time Limit:                                | Estimate Cost:  |                    |
| AMOUNT              | 7,600.<br>Three Mont   | 3,79,219.   |                    |

Qty. 48.47

**Figures** 

Words

Rs. P

Per cubic

No.

Earth work in excavation for structures in all depths as per drawing and M.O.R.D.technical

Name of Work (SH: Construct

| e | metre | 66.60 | stone aggregate 40 mm (forty milimeters) nominal size) plums and curing complete including the cost of form work in <b>Retaining walls Breast walls</b> , in or under water complete including, pumping or bailing out water ,dewatering removal of slush as required at site which may arisen at the time of laying under water complete for all heights/depths including cost of form work as per drawings and MORD technical specifications section 800, 900,1200 & 1600 and as per the direction of Engineer-in-Charge including carriage of material within all leads and lifts and other incidentals.  |    |
|---|-------|-------|--|----|
|   |       |       | dressing of sides and bottom and back filling in trenches with excavated Suitable materials. All work of rock cutting by blasting shall be carried out by taking all necessary precautions against soil erosion, damage to hill side, water pollution etc. and to protect stability of hill side rock shall be excavated with chiseling and wedging out rock (where blasting is prohibited). All earth work in cutting/excavation including rock excavation shall be carried out true to lines grades, side slopes, width, camber super elevation and level as shown on the drawings or as directed by the Engineer-in-Charge, hauling and stacking of materials useful for construction at suitable sites and safe disposal of unsuitable cut materials in specified manner, filling of unevenness and finishing the road to specified dimension or as directed by the Enginer-in-Charge. If the foundation of the structure is in an area with stagnant water or water is met with in the excavation due to spring seepage, rain and other causes it shall be removed by suitable diversion, bailing out or pumping as directed and the area of the foundation or embankment shall be kept dry. Any loss to the public or private property during the course of excavation shall be the whole responsibility of the contractor which shall have to be duly compensated by him at his own cost. |    |
| o | metre |       | specification section 300 & 1600 including setting out, construction of shoring and bracing,   | 10 |

|         |      |        | Total   |     |
|---------|------|--------|---|-----|
| į       |      |        | incidentals and to the entire satisfaction of the Engineer-in-Charge.                             | T   |
|         |      |        | of Engineer-in-Charge including carriage of material within all leads and lifts and other         |     |
|         |      |        | drawing and M.O.R.D.technical specification clauses 614, 709 & 1206.6 and as per the directions   | Y   |
|         |      |        | the full width of the structures with slope of I (v): 20(H) towards drainage face complete as per |     |
|         |      |        | wing wall, return wall with 100mm (one hundred millimeter) dia P.V.C. pipe extending through      |     |
|         | Each | 55.00  | Providing weep holes in brick masonry/stone masonry/plain or reinforced concrete abutment,        | w   |
| Figures |      | Qty.   | 0.  | NO. |
|         | Unit | No. or | Description of work   | 1   |
|         |      |        |   |     |

Executive Engineer
B & R Division HP.PWD,
Joginden Nagar