

Office of the Executive Engineer Electrical Division, HP PWD Una Tel: +911975223484, Fal: +911975223484

E-mail: ee-eleu-hp@nic.in

08-08-2027

No.PW/EDU/CB//TA/e-tender/2023-24/- / 489 - 150-9

Dated

To

The Executive Engineer (IT) Cell. Nirman Bhawan, Nigam Vihar Shimla-171002

Subject:

Regarding publication of Tenders Notice.

Sir.

"JAI HIND"

Enclosed please find herewith Tenders Notice along with Schedule of Quantities for uploading the same on Departmental website as per Notification no. PBW-(B)1/2020 dated 16.07.2021 as the work mentioned in the Tender Notice are urgent in nature and in Public interest. This is for your kind information and necessary action at your end please.

DA:-As above.

Executive Engineer, Electrical Division, APPWOR Unn.

Copy along with its enclosures is forwarded to the following for favour of information please:-

- 1. The Superintending Engineer, 2nd Electrical Circle, HPPWD, Dharamshala.
- 2. The Assistant Engineer, Electrical Sub Division, HP PWD Hamirpur/Una & Bilaspur.
- 3. All the contractors working under the control of this Division.
- All the Head of Branches in this office.
- Notice Board.

Executive Engineer, **Electrical Division** HPPWD, Una



Office of the **Executive Engineer** Electrical Division, HP PWD Una Tel: +911975223484, Fax: +911975223484

E-mail: ee-eleu-hp@nic.in

No.PW/EDU/CB//TA/tender/2023-24/-

1397-1422

The Director. Information & Public Relation Deptt., H. P. Shimla-171002.

Subject: -

Regarding publication of tenders notice.

Sir,

"JAI HIND"

Enclosed please find herewith tenders notice for publication in Giriraj/Tribune/ Punjab Kesari/Hindustan Times Newspaper as well as in the other reputed/ leading newspapers on or before 07.06.2023, at the earliest under intimation to this office please.

DA:-As above.

Executive Engineer, Electrical Division, IPPWD, Una.

Copy along with its enclosures is forwarded to the following for favour of information please:-

The Engineer-in-Chief, HPPWD., Shimla-2.
 The Superintending Engineer, 2nd Electrical Circle, HPPWD, Dharamshala.

- 3. The Assistant Engineer, Electrical Sub Division, HP PWD Hamirpur/Una & Bilaspur.
- All the contractors working under the control of this Division.
- Drawing Branch in this office.
- Notice Board.

Executive Engineer, Electrical Division, HPPWD, Una

PUBLIC WORKS DEPARTMENT

CORRIGENDUM

The Offline tenders for Job No. 1 to 24 has been called vide this office Letter No. PW/EDU/CB/TA/Tender/2023-24/- 1397-1422 dated 30.05.2023 and published in Giri Raj vide Released order No. 0965/2023-24 (Classified) dated 07-06-2023, and the bids which are to be opened on dated 17.06.2023 at 11:00 A.M. Out of which the Job No. 06 and 07 there are corrections in the NIT and Job No. 22 there are some corrections in the DNIT as per the detail given below:-

Sr. No.	Job No.	Name of Work	Estimated. Cost (In Rs.)	Earnest Money (in Rs.)	Time Limit	Cost of form (In Rs.)	Eligibility of Contractor
1	06	R/M of E.I in various N/R buildings under ESD Hamirpur Distt Hamirpur HP (SH:- Providing inverter in rest house sera therein.)	Rs. 1,34,257/-	Rs. 2,700/-	Six Months	350/-	May be read as Specialized Job instead of Class-D,C
2	07	R/M of E.I in various N/R building under ESD Hamirpur Distt Hamirpur HP (SH:- Providing air conditioner in rest house sera Therein.)	Rs. 2,72,697/-	Rs. 5,500/-	Six Months	350/-	May be read as Specialized Job instead of Class-D,C
3	22	C/o New Canteen at Govt. College Beetan, Distt. Una (HP) (SH:- Providing E.I. therein)	May be read as Rs. 2,37,147/- instead of Rs. 2,00,754 /-	May be read as Rs. 5,000/- instead of Rs. 4,000/-	Six Months	350/-	Class-D,C

Rest of terms and conditions shall remain unchanged.

HIM SUCHANA AVAM JAN SAMPARK

Executive Engineer, Electrical Division, HPPWIPUna. Dated 08/06/2023

No-PW/EDU/CB/TA/Tender/2023-24/- 1510-30

Copy forwarded to the following for information and necessary action:-

- The Superintending Engineer 2nd Electrical Circle HPPWD Dharamshala.
- All the Assistant Engineers working under this Division.
- 3 All the Head of branches of this office.
- All the contractors working under the control of this Division.
- Notice Board.

Executive Engineer, Electrical Division, HPPWD Una.

HIMACHAL PRADESH PUBLIC WORKS DEPARTMENT

*Office Order *

The tender for job No. 1 to 24 called vide this office letter No. PW/EDU/CB/TA/Tender/2023-24/- 1489-1509 dated 08.06.2023 and published in Giri Raj and published in Giriraj vide Released order No. 0965/2023-24 (Classified) dated 07.06.2023 which were to be sold on 15.06.2023 and were to be opened on 17.06.2023 at 11.00 A.M. The date of sale and date of opening for these tenders is hereby extended, now the same will be sold on 23.06.2023 and opened on 26.06.2023 at 11:00 A.M. due to administrative reason. Rest of terms and conditions shall remain unchanged.

HIM SUCHANA AVAM JAN SAMPAR

No-PW/EDU/CB/TA/Tenders/2023-24/-

Executive Engineer, Electrical Division

Dated:-

Copy forwarded to the following for information and necessary action:-

- 1. Superintending Engineer. 2nd Electrical Circle HPPWD., Dharmshala.
- 2. All the Assistant Engineers working under this Division.
- 3. All the Head of branches of this office.

Notice Board.

Executive Engineer, Electrical Division HPPWD., Una

DRAFT SCHEDULE OF QUANTITY

Job No. 1

Earnest money:- Rs. 5,800/-

Time Limit: One year.

(SH Providing E.I.there in) NAME OF WORK :- C/O Health Sub Center in Jagan Nath Mandir In G.P Rajpura Jaswan Tehsil Amb Distt. Una (HP)

3.03	3.02	3,01	og Line	2	1.01	-	S. No.
4x4 Sq. mm.+2 X 4 sq. mm earth wire	2x4 Sq. mm.+ 1 X 4 sq. mm earth wire	2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Finolex,KEI,Anchor,Plaza make)	Wiring for light plug with 2x1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq.mm. HRFRI SEPVC insulated single core copper conductor cable for earthing as required (Finolex, KELAnchor, Plaza make)	Group C. ▶	Wiring for light point / fam point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required.(SSK,Anchor,L&T make)	Description
32	4	40		40	44	- Treat	Quantity
671	416	301		301	1480		Fig.
Rupees Six hundred seventy one only.	Rupees Four hundred sixteen only.	Rupees three hundred one only.		Rupees three hundred one only.	Rupees One thousand four hundred eighty only.		III words,
P/mtr.	P/mtr.	P/mtr.		Pimit.	Each		CBIE
21472	18304	12040		12040	65120		Amount

1264	Each	Rupees Three hundred sixteen only	316		Supplying and fixing metal box of 180nunx100nunx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 15/16 amps socket outlet and 15/16 amps, piano type switch, connections, painting etc. as required. (SSK, Anchor, L&T make)	
868	Each	Rupees Two hundred seventeen only.	217	•	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, piano type switch, compositions, painting etc. as required (SSK, Anchor, L&T make)	
2398	Each	Rupees One thousand one hundred ninety nine only.	1199	2	Supplying and fixing Power plug socket with MCB Protection 25 Amps with Plug top and 4 Module box including making connections, testing etc.as required (SSK ,Cat.No.PSM-1501,HSN Code 8536/Anchor/ L&T make)	7
381	Each	Rupees three hundred eighty one only.	381	-	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase,230 volts complete as required:Make:- Legrand, L&T, Anchor as approved by Engineer-in-charge.	6
240	Each	Rupees Sixty only.	60	4	Supplying and fixing bakelite batter/angle holder including connections etc. as required:-	i,
1940	P/mtr.	Rupees Ninety seven only.	97	20	3x1.5 Sq. mm.	4.01
0					Supplying and drawing following size of PVC insulated, beat resistant, flume retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed, Steel/PVC conduit as required (Finoles, KELAnchor, L&T make)	4
1406	P/mtr.	Rupees Seven hundred three only.	703	12	2x10 Sq. nm.+ 1 X6 sq. mm earth wire	3.05
20340	P/mtr.	Rupees Five hundred sixty five only.	565	36	2x6 Sq. mm.+ 1 X6 sq. mm earth wire	3,04

2130	P/mtr.	Rupees seventy one only.	71	30	Supplying and laying 6 SWG G.I. wire at 0.50 mtr. below ground level for earth electrode conductor, including soldering etc. as required.	5	The second
	Sin Gr	The state of the s		1	watering pipe etc. Cour with criarcoal of coxe and sair J complete as required.	April 1	1
1	100	thirty one only.	1570		providing masonry enclosure with cover plate having locking arrangement and		
13.67		forty seven only.	1100		Backles with C I work aim A C was Para and A Company in the Carlo and A Com		
3890	Each	Rupees One thousand aine hundred	1943	2	Double door-12 way	13.01	Of the
	STATE OF THE PARTY				distribution board, 240 volts; on surface / recess, complete with tinned copper bus- bur, wire-set, neutral tink, earth bar, din-bar, detachable gland plate, blanking plate, cable, identification labels interconnections, phosphatized and powder painted, including earthing etc. as required:-L&TYABB/Legrand		
division D	SAPTIONS:	HILL THE REAL PROPERTY AND ADDRESS OF THE PARTY AND ADDRESS OF THE PART	-	The Cappe	Supplying and fixing of following way, single pole and neutral sheet steel MCB	mid po	1000年十七日
5814	Each	Rupces Two thousand nine hundred seven only.	2907	2	63 Amps. Cat-A.	12.01	
0	4. 5-36			*1	Supplying and fixing following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB), having a sensitivity current up to 300 miliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required. L&T)/ABB/Legrand	12	
944	Each	Rupees Four hundred seventy two only.	472	2	Double pole, Cat-A.	11.01	
0	23				Supplying and erection of 40/50/63 amps rating, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-L&T)/ABB/Legrand	=	
3458	Each	Rupees Two hundred forty seven only	247	14	Single pole. Cat-A.	10.01	
					Supplying and erection of 6 amps. to 32 amps. rating, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-L&T/ABB/Legrand	10	\

1. 在 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	131			
19	=	17	16.01	16
Supplying and fixing LED-Tube fixture 20 wants surface mounting with polycabonate diffuser with extruded aluminium housing and it should be compatible with specification i.e 2000 Lumen output, 80, 6500 K, length 4 feet Beam angle 120 degree suitable for input voltage 150-270 volts 50 HZ. Surge rating upto 3 KV, complete with all accessories connections, testing and commissioning etc. as required (Wipro Trim Neo LL20-281-XX-65AL1/Philips/ OSRAM make),	Supplying and fixing surface LED 12 wan round down lighter with high efficacy. Housing made of extruded aluminium with high translucent HET diffuser and it should be compatible with specifications i.e. Power factor >0.9, Harmonic distortion <10% & efficacy >100 Lumen per want, CRI >80,6500 K suitable for input voltage 220-240 Volts, 50 Hz, IP rating 20, Surge rating up to 2 KV, Dia 140mm complete with connections etc., as required. Wipro Iris Slim Surface mounted LD-80-101-XXX-60-SM (Philips or OSRAM make)	Supplying and fixing Fan box of M.S.sheet with iron rod hook 12 mm.in place of junction box complete as required.	Ceiling Fan 1200 mm sweep, Category-A	Providing, Installation, testing and commissioning of ceiling fan with step type fan regulator modular, air delivery 215 m3 /min power input 30 watts speed 330 RPM, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required:-(Category-A(Crompton WWHE ISI mark/WHE ISI mark)/Usha Technix Plus/Bajaj
	10	7	7	
1238	1584	2	2872	
Rupees One thousand two hundred thirty eight only.	Rupees One thousand five hundred eighty four only.	Rupees Forty four only.	Rupees Two thousand eight hundred seventy two only.	
Each	Each	Each	Each	
13618	15840	308	20104	

24.01	24	23	8	21	18
Exhaust Fan, Heavy duty, 300 mm sweep	Providing and installation of exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required:- Crompton 300mm Drift Air Plus Metal Anti Dust)/Usha	Providing and Installation of Wall mounting fan of 400 mm sizes i'e hang the same in position on the wall, connections, testing and commissioning etc.as required Make:- Lisha(Striker-Hi-speed), Crompton HIFLO NEO/Bajaj as approved by Engineer-in -charge.	Supplying and fixing of fancy wall bracket of model Cat.No.37934 chrome finish colour with opal glass diffuser made of mild steel, containing thread type LED lamp holder(s) of all sizes and shupes, complete with all accessories but excluding led lamp including making connections, testing etc. as required.: Make Philips,Jaquar Tisva as approved by Engineer in -charge.(Five year warranty)	Providing and fixing LED Street light 25 watts aesthetic aluminium powder coated housing ,with Precise optical LENS for uniform light distribution ,AC 85-270 volts ,available color temperature 5700 K,CRI 80,IP rating 66, up to 10KVA electric surge protection and bracket of steel conduit pipe 32 mm., complete with all accessories, connections, testing and commissioning etc, as required. (Wipro LR06-311-XXX-57-XX/Ctair/Philips make)	Supplying and fixing LED Tube fixture 40 watts surface mounting with polycarbonate diffuser with aluminium housing and it should be compatible with specification i.e 4000 Lumen output, CRD-80, 5000-5700 K, length 4 feet Beam angle 120 degree saliable for input voltage 150-270, volts 50 HZ. Surge rating upto 3 KV, IP40 complete with all accessories connections, testing and commissioning etc. as required (Wipro optima LL24-541-XXX-57-XX/ Philips/OSRAM make),
		-	2	13	121
2753		3307	2385	4653	2574
Rupees Two thousand seven hundred fifty three only.		Rupees three thousand tihree hundred seven only.	Rupees Two thousand thee hundred eighty six only.	Rupees Four thousand six hundred fifty three only.	Rupees Two thousand five hundred seventy four only.
Each		Each	Each	Each	Each
11012		3307	4770	9306	5148

		-			Total:-	
Rupees Two hundred sixty four	2	Rupe	264	80	armoured cable 10 sq. mm (Twin core)	27.01
					Providing and laying of aluminium conductor, PVC insulated and PVC sheathed, armoured/XLPE power cable, working voltage 1100 volts grade direct in ground to be laid 1 meter below the ground level including excavation and refilling the trench etc.as required, but excluding sand cushioning and protective covering etc. of required size:-Havells/KEI/Plaza make)	27
Rupees One hundred fifty nine only.	2	Rupe	159		S/F LED lamp 9 watts Philips/Havells make in the existing batten holder, wall bracket, bulk head fitting & bath room bracket etc, as required.	26
Rupees Four hundred sixty four only.	- 2	Rupe only.	461	4	25 Supply and fixing exhaust fan Louver shutter for 300/380mm exhaust fan on the existing wall painting including 12 mm thick wooden ply board for suitable size of exhaust fan hole. National or its equivalent make	25

Executive Engineer, Electrical Division, HP-PWD_Una.

DRAFT SCHEDULE OF QUANTITY

Estimated costs- Rs. 1,37,7085-Earnest moneys- Rs. 2,8000-

NAME	NAME OF WORK (- C/O Holipad at Sanghnus, Tebsii Ghanari Distr.Una (HP) (MI :-Providing E.L.therein).	Ltherein).				-
S. Vo.	Description	Quantity R	Rate In	In words.	Call	
-	Witing for light point / far point / exhaust far / call hell point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed sacel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required.(Maked.egrand, L&T., Anchor)					
1.01	Group C.	*	1666	Rupees One thousand six hundred of sixty six only.	Each	
	Wiring for light plug with 2x1.5 Sq. nun. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq.nun. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Fipolex, KFLApchor, Plaza make)	15	315	Rupces three hundred fifteen only.	Plant.	
	Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame estardant (HRFR) and low amoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1-No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Flaolex, KEL, Anchor, Plaza make)	*	\$	Rupees four hundred forty five only.	P/intr.	AND DESCRIPTION OF THE PARTY OF
-	Wiring for power plug with 4x4 Sq. mifc PVC institued heat resistant flame retardam (HRFR) and low sinuke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 2 No.4 Sq.mm. HRFRJ.S/PVC insulated single core copper consluctor cable for earthing as required (Finolex,KEI,Anchor,Plaza make)	5	7	Rupees Seven hundred fourteen only.	P/mtr.	

	3	1	J. J. J-(81)	17.1	11.37	Marine St.					
12.01	12	10.11	п	10	9		7	6.01	0	10.5	(A
Double pole, Cal-A.	Supplying and crection of 40/50/63 unps rating, 10 KA breaking espacity, 240 volts, 'C' curves, ministure circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-	Single pole. Cat-A.	Supplying and crection of 6 tamps, to 32 amps, rating, 10 KA breaking capacity, 240 volts. 'C' curves, miniature circuit breaker of following poles in the existing MCB-DB complete with connections etc. as required;(Make:-Legrand , L&T ,Hagger)-	Supplying and fixing bakefee batten haigh bolder including connections etc. as required.	Supplying and fixing Ding-Dung / Electronic musical bell, suitable for D.C./A.C. single phase, 230 volts complete as required. (SSK, Anchor make)	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic luminated sheet cover in the front including providing and fixing 6 pin 15/16 amps socket outlet and 15/16 amps, piano type switch, connections, painting etc. as required (SSK_AnchorfL&T make)	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenelic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, plano type switch, connections, painting etc., as required.	3x1.5 Sq. mm.	Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed. Suet/PVC conduit as required (Finoles, KELAnchor, Plaza make)	2x1.5 Sq. mm.	Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No. HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required (Finoley, KELAnchov, Plaza make)
1	Dig.	7		4	4	-		10	٠.,	z	
469		191		62	379	529	2	100		315	
Rupoes Four hundred sixty nine	Approximately and the second	Rupees One hundred ninety one only.		Rupees sixty two only.	Rupees (three hundred severity nine only.	Rupees Five hundred twenty nine only.	Rupees four hundred four only.	Rupees One hundred only.		Rupees three hundred fifteen only.	
Each	-	Each		Ench	Each	Each	Each	P/nstr.		Phate.	
469		1337	1	124	379	2116	1212	1000		8505	-

7	80.2							-	
19	10.81		17	16	- 5	14.01	E E	13.01	5
Supplying and fixing Fan box of M.S.sheet with iron red hook 12 mm.in place of junction box complete as required.	Ceiling Fan 1200 mm sweep, Category-A	Providing, Installation, testing and commissioning of ceiling fan with step type fan regulator modular, air delivery 215 m3 (min power input 30 watts speed 330 RPM including wiring the down rods of standard length (up to 30 cm) with 160.20 mm twin twisted flexible, cousm braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fair bow and curthing etc. 26 required (Crampton WWHE ISI mark/Usha-Technixplus BEE 3star/ Bajaj 3 Star rated model)	Supplying and laying 6 SWG G.I. wire at 0.50 mir. below ground level for earth electrode candisctor, including soldering etc. as required.	Extra for using salt and charcool for pipe earth electrode complete as required.	Earthing with GJ carth pipe 4.5 mtr, long and 40mm dia, including accessories and providing mannersy enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal or coke and salt) complete as required.	Double door-12 way(Make:- Legrand , L&T , Hagger)-	Supplying and fixing of following way, single pole and neutral sheet steel MCB distribution board, 240 volts, on surface I recess, complete with tinued copper bus- bar, wineset, neutral link, earth box, din-bar, detachable gland plate, blanking plate, cable, identification labels inserconnections, phosphatized and powder painted, including earthing eac as required:	63 Amps. Cal-A.	residual current circuit breaker (RCCB), having a sensitivity current up to 300 millampers in the existing MCB DB complete with connections, testing and commissioning etc. as required. (Maker-Legrand, UAT, Hugger).
2	.2		25	_	-	-		-	
#	2872		67	1745	5574	1731		2938	
Rupees forty four only.	Rupees Two thousand eight		Rupees sixty seven only.	Rupees One thousand seven hundred forty five only.		Rupees One thousand seven hundred thirry one only.		Rupoes Two thousand nine hundred thirty eight only.	
Each	Each		Pintr.	P/set	Piset	Each		Each	
82	5744		1675	1745	5574	2691		2938	

	1	št.	N	Section of the Party and Section 19	The second second	22,01	E	TI.	20
on the existing wall complete with connections lesting and commissioning etc.as required.(Crompton HIFLO NEO/Usha make (WF)Mist Air DUOS/Icy blue/Bajaj.)	County for and Spins Cubinford See 400 week 2000 and 200 and 200 127 high second	Supplying and fixflig Power plug societ with MCB Psylection 23 Amps with Plug top and 4 Module box including making connections, testing etc. as required (SSK "Cat.No.PSM-1501.HSN Code 8536/Anchorf L&T make)	S/F Computer board comprising 3 No.5 amps.switch (P/T) and 3 No.3 pin 5 amps. Socket out let (P/T) and 1 No.200x250x100mm metal box with cover plate and 1 No.4 modular switch board with cover plate and 1 No.computer jack with shutter including connections etc., as required, complete in all respects. (L&T/SSK/Anchor make)	wall painting etc. at required (National or its equivalent smalle)	Supplying and fixing exhaust fan louver shutter for 300 num.exhaust fan on the existing	Exhaust Fan, Semi Commercial, 300 mm sweep	Providing and installation of exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required: (CromptonSemi Commercial Double Ball Bearing/Ugha - SPH Turbo HDEF 900 RPMISI/Bajaj)	Providing and fixing LED surface/pendent mounting Tube fixture 36 watts. LED batters involved aluminium bouning PC diffuser with PC end caps.spring steel clamps for surface mounting arrengement and it should be compatible with specifications i.e.Power factor =0.9,Harmonic distortion <10% & efficacy >100 Lumen per watts,CR1 >80,5700 K suitable for input voltage 220-240 Volts,50 HZ, Length 1175X30X36 mm.complete with connections and as per best satisfaction of Engineer-to-Charge complete as required.(Panassonic Harrows Al Code No./PBTM08368/Philips/Wipro maske)	Supplying and fixing LED Batters 10 wasts. Mirror Light, and it should be compatible with specifications i.e power factor=0.9. Hurmonic discortion=10%& efficacy=100, lumon per watts, CR1>80, CCT 6500K suitable for input voltage 150-270 volts, 50Hz, IP rating 20, surge rating 2.0%x, and longth 59.5 cm complete with connections etc. as required (Wijero Trim. Neo LL-20-111-XXX-65NE2/Tisva /Philips make)
					1	1		-	-
200	1	1221	\$20		449	3246		1801	6,90
hundred seven only.	District the state of the state	Rupees One thousand two hundred nacety only.	Rupees Eight hundred twenty only;	ordy	Rupees Four hundred forty nine	Rupees three thousand two hundred forty six only		Rupees Ose thousand eighty one only.	Rupees six hadred thirty only.
	1	Each	Each	Section of the last	Each	Each	v J	Dach	Each
200	LUCE	1221	820	The second second	- 449	3246	- 31	434	630

						-	
77,772,8555			Section 19 and 1				
1000	31		30	29	28.01	2.8	27
required.(Philips Ace Saver HSN CODE 85395000/Tisva/Panasonic make)		watts CRL>80-5700 K suitable for input voltage 220-240 Volts, 50 Hz, IP rating 20, Surge rating up to 2 'KV, Dia 169mm complete with connections etc, as required. Panasonic PDLM26188 (Jaquar, Philips or its equivalent make)	Supplying and fixing surface LED 18 watt round down lighter with high efficacy. Housing made of casted aluminium housing with SS Strips and it should be compatible with specifications i.e. Brownerfactor > 0.9 Harmonic distortion < 10% & efficacy > 100 burner per	Providing and fixing LED streetLight 30watts CCT 5700K, CRI>80, Surge rating 5kv, IP 66, input voltage140V-270v,50Hz,A.C.Supply with M.S. bracket 62 mm. dia with die cast aluminium housing with IP diffuser on the existing pole including connections complete in ull respects and best satisfaction of Engineer -in-charge at site (Panasonic Cat.NoPSTM27308XX/Philips/Wipro make)	Storage water heater, 25 Liter capacity Cat-A Jaquar (Elena verticall/Recold Min 4 star	Providing and installation of stationary storage type Electric water heater (Geyser) vertical 25 ltrs capacity by means of Expansion-bolts with nuts and washers, including embedding of expansion-bolts in the wall, providing and fixing of Non-return valve, Dead weight safety valve, 2 No C.P. connection rods 18" long, making good the damages, electrical connections, safety valve connections, testing and commissioning etc. as required: (Jaquar/Recold make)	Supplying and fixing of sub main wiring with 10 sq.mm.weather proof twin core aluminium conductor cable on the G.I.bearer wire etc.as required(,Polycab,Havells,Finolex)
	2		2	ω	-		30
	151		1094	3911	12450		71
only	Rupees One hundred fifty one		Rupees One thousand ninety four only.	Rupees three thousand nine hundred eleven only.	Rupees Twelve thousand four hundred fifty only.		Rupees Seventy one only
	Each		Each	Each	Each		P/mtr.
	302		2188	11733	12450		2130
	required (Philips Ace Saver HSN CODE 85395000/Tisva/Panasonic make)	31 Supplying and fixing LED Lump 9 watts 825 Lumens 240 volts AC supply 50 Hz in the 2 151 Rupees One hundred fifty one existing batten-holder, wall bracket & bulk-head fitting etc. as required (Philips Ace Saver HSN CODE 85395000/Tisva/Panasonic make)	watts, CRL>80.5700 K suitable for input voltage 220-240 Volts, 50 Hz. IP rating 20, Surge rating up to 2 KV. Dia 169mm complete with connections etc., as required. Panasonic PDLM26188 (Jaquar, Philips or its equivalent make) 31 Supplying and fixing LED Lamp 9 watts 825 Lumens 240 volts AC supply 50 Hz in the existing batten-holder, pendent holder, wall bracket & bulk-head fitting etc. as required (Philips Ace Saver HSN CODE 85395000/Tisva/Panasonic make)	Supplying and fixing surface LED 18 watt round down lighter with high efficacy. Housing made of casted aluminium housing with SS Strips and it should be compatible with specifications i.e. Rowner factor >0.9. Harmonic distortion <10% & efficacy >100 Jumen per watts, CRL>80.5700 K suitable for input voltage 220-240 Volts, 50 Hz. IP rating 20, Surge rating up to 2 "K V. Dia 169mm complete with connections etc., as required. Panasonic PDLM26188 (Jaquar, Philips or its equivalent make) 31 Supplying: and fixing LED Lamp 9 watts, 825 Lumens 240 volts AC supply 50 Hz in the existing batten-holder, wall bracket & bulk-head fitting etc. as required. Panasonic make)	29 Providing and fixing LED streetLight 30watts CCT 5700K, CRD>80, Surge rating \$kv, IP 66 3 3911 Rupces three thousand nine input voltage 140V-270v,50Hz, A.C.Supply with M.S. bracket 62 mm. dia with die cast aluminium housing with IP diffuser on the existing pole including connections complete in all respects and best satisfaction of Engineer -in-charge at site (Panasonic Cat.NoPSTM27308XXPhilips/Wipro make) Supplying and fixing surface LED 18 want round down lighter with high efficacy. Housing made of casted aluminium housing with \$S Strips and it should be compatible with specifications i.e.Rower factor > 0.9 Harmonic distortion < 10% & efficacy. > 100-bunner.per wants CRL>80, 5700 K suitable for input voltage 20-240 Volts, 50 Hz, IP rating 20, Surge rating up to 2: Kv Dia 169mm complete with connections etc, as required. Panasonic PDLM26188 (Jaquar, Philips or its equivalent make) 31 Supplying and fixing LED Lamp 9 wants, \$25 Lumens 240 volts AC.supply 50 Hz in the existing batter-holder, pendent holder, wall bracket & bulk-flead fitting etc, as required (Philips Ace Saver HSN CODE 853950007 fsva/Panasonic make) 32 Supplying Ace Saver HSN CODE 853950007 fsva/Panasonic make)	Storage water heater, 25 Liter capacity Cat-A Jaquar (Elema vertical)/Recold Min 4 star 29 Providing and fixing LED streetLight 30watts CCT 5700K, CRD-80,Surge rating 5kv, IP 66 input voltage 140V-270v,50Hz,A.C.Supply with M.S.bracket 62 mm.dia with die cast aluminium housing with IP diffuser on the existing pole including connections complete in all respects and best satisfaction of Engineer-in-charge at site (Panasonic Cat.NoPSTM27308XX/Philips/Wipro make) 30 Supplying and fixing surface LED 18 watt round down lighter with high efficacy. Housing made of casted aluminium housing with SS Strips and it should be compatible with specifications is Rower/heav-9.03/Lumonic distribution <10% & efficacy >100 Lumony = 1094. Rupces One thousand ninety four Each populations is Rower/heav-9.03/Lumonic distribution <10% & efficacy >100 Lumony = 1094. Rupces One thousand ninety four Each populations is Rower/heav-9.03/Lumonic distribution <10% & efficacy >100 Lumony = 1094. Rupces One thousand ninety four Each populations is Rower/heav-9.03/Lumony = 1094. Rupces One thousand ninety four Each populations is a complete with connections etc, as required. Panasonic PDLM26188 (Jaquar, Philips or its equivalent make) 31 Supplying and fixing LED lamp 9 wats. 825 Lumony 249 volts. AC.surpply 50 Hz. in the existing batter-holder, part HSN CODE 85395000/Tisva/Panasonic make) 32 Rupces One hundred fifty one Each only.	Providing and installation of stationary storage type Electric water heater (Geyser) vertical 25 lits capacity by means of Expansion-bolts in the stall, providing and fixing of Non-return valve, Dead weight safety valve, 2 No.C.P. connection rods 18 Yourg, making good the demages, electrical connections, safety valve connections, testing and commissioning etc. as required:—(Jaquar (Elena vertical))/Recold Min 4 star 28.01 Storage water heater, 25 Life: capacity C-2t-A Jaquar (Elena vertical)/Recold Min 4 star Providing and fixing 1.ED streetLight 30watts CCT 5700K, CRID-80,Surgy raing 5kv, IP 66 input voltage140V-270v, 50Hz, A.C.Surphy with M.S. bracket 62 mm.d.da with die cast aluminium housing with IP diffuser on the existing pole including connections complete in all respects and best satisfaction of Engineer-in-charge at site (Panasonic Can-Vol's)71117308X/Vibilips/Wipro make) Supplying and fixing surface LED 18 wat round down higher with high efficacy. Housing surface Lebence feater-24 plarmonic distortion <10x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 520 K voltage 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 520 K voltage 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value (CLESS) 40x4 College 20x1-24 Voles, de Elibacy >100 Lumen per value

Executive Engineer, Electical Division, HPPWD Una.

5907	Rupees if we hundred ninety three enty.	393	9	exhaust fan on the existing wall painting including 12 mm thick wooden ply board for suitable size of exhaust fan hole.	i.
Each	Rupees three thousand six hundred eighty two only.	3682	9	Exhaust Fan, Heavy duty, 300 mm sweep	2.01
				Providing and installation of exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required. Make: Usha , Crompton or its equivalent as approved by Engineer-in - charge.	2
Each	Rupees Two thousand eight hundred	2895	Ж	ceiling fan 1200 mm	1.01
				Providing installation testing and commissioning of ceiling fan with step size socket size regulator, including wiring the down rods of standard length (up to 30 cm) with 16/0.20 mm twin twisted flexible cotton braided copper cable including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc as required. Make:- Usha Technix plus, or its equivalent not less than three star rating or its equivalent as approved by Engineer-in - charge.	-
Unit	In Words.	Rate In	Quantity	Description of Items	No.
ysers	(SH:- Providing accessories "LED Fixtures, fans, Geysers	(SH :- Pro	tirpur (H.P)	Name of work :- C/O Primary Health Center Building at Rail Distt, Hamirpur (H.P) etc. there in)	Name of work
	Time Limit: Six months.				
	Earnest money:- Rs. 7,400/-				
	Estimated cost:-Rs. 3,67,907/-				
	Job No. 03			DRAFT SCHEDULE OF QUANTITY	

	0.	CA.	4
watt suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.as required. Make: Panasonic (Code: PBLM15368)), Jaquar, Philips, wipro of its equivalent as approved by Engineer-in-Charge.	Supplying and fixing surface mounting 1'x4' size 36 Watt LED surface mounted base light comprises of CRCA housing luminaire LED 36 watt 5700 K with five year warranty and it should be compatible with specification i.e Power Factor > 95 Harmonic Distortion (10% and efficacy) 100 Lumens per 95 Harmonic Distortion (10% and efficacy) 100 Lumens per	S/F of Cabin/wall fan 400 mm Mist Air on the existing wall complete with connections,testing and communissioning etc, as required. Make:- Usha, crompton or its equivalent as approved by Engineer-in - charge.	Supplying and fixing of Exhaust fan (Plastic) with Louver shutter 300mm 1000RPM '1125 Air Delivery Ex fan on the existing opening including making the hole to suit the size of above fan making good the danmages complete with connections, testing and commissioning etc. as required. Make :- Usha, Crompton, or its equivalent as approved by Engineer-in-Charge.
	6	-	10
	7688	2734	2850
	Rupees Seven thousand six hundred eighty eight only.	Rupees Two thousand seven hundred thirty four only.	Rupees Two thousand eight hundred fifty only.
	Each	Each	Each
	46128	2734	28500

9	00	-1
Supplying and fixing surface square type LED: 15: watt, 6000k; (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9, Harmonic Distortion<10% and efficacy > 100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make: - Panasonic/Philips, wipro or its equivalent as approved by Engineer-in-Charge.	Supplying and fixing LED Batten 10 wait ,6500k ,(Five YEAR WARRANTY) and it should be compatible with specification e.i. Power Factor > .9, Harmonic Distortion<10% and efficacy > 100 Lumens per wait, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.Make - Jaquar/Panasonic /PHILIPS , wipro or its equivalent as approved by Engineer-in-Charge	Providing and fixing of surface mounted Luminaire LED 24 Watt batten, having high Quality design aluminium extruded decorative end caps with (Five year warranty) and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion <10% and efficacy >100 Lumens per watt ,CRI> 80 suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.as required .Make :- Panasonic, Jaquar, Philips, wipro or its equivalent as approved by Engineer-in-charge.
40	12	36
1065	363	595
Rupees One thousand sixty five only.	Rupees three hundred sixty three only.	Rupees Five hundred ninety five only.
Each	Each	Each
42600	4356	21420

Supplying and for 10/100/1000 port (green ethernet) I switch that delive increasing the spoprotocol storing a	(tinted,toughened with U-marking wit	Supplying and fit warranty) with it aluminium heat s specification e.i. per wan, CRI> 8 50/60Hz, comple commissioning e /Philips/sor its eq	Supplying and fit (Five YEAR W/ specification i.e. and efficacy > 10 AC 220-240 V, 5 connections, test Philips, wipro of Charge.
Supplying and fixing D- link DGS-1100-08 (8 Port) 8- 10/100/1000 ports EasyL2 switch standalone switch in desk top (green ethernet) for getting blazing speed of Gigabit Ethernet L2 switch that delivers power performance and reliability i.e increasing the speed of net work server in large in switching protocol storing and forwarding as required .Make:- D-Link.	Supplying and fixing of wall-mounted 2U-rack sizes 550x400 mm depth including its complete accessories i.e. front glass door (tinted toughened) with lock&key, 2 pairs pf 19" mounting rails with U-marking welded side walls 1U cable manager(1), hardware packet (1pkt), 3 socket 5 amp, power distribution unit (1 No) as per product code NWR-4U-5040-GR as required. Make:- D-Link.	Supplying and fixing of LED 45. Watt street light (five year warranty) with innovative & sesthetic & robust design with aluminium heat sink and toughened glass (IP 66) with specification e.i. Power Factor > .9, and efficacy > 100 Lumens per watt, CRI > 80 suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. as required. Make -Parasonoic, Jaquar /Philips/sor its equivalent as approved by Engineer-in-Charge.	Supplying and fixing Square LED Recess type 20 watt, 6000k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9, Harmonic Distortion<10% and efficacy > 100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:- Partasonic/Phillips, wipro or its equivalent as approved by Engineer-in-Charge.
1		· ·	4 4 4 4 4
5453	2963	2484	1578
Rupees Five thousand four hundred fifty three only.	three only.	Rupces Two thouisand four hundred eighty four only.	Rupees One thousand five hundred seventy eight only.
Each	Jach	Each	Each
5453	1982	7452	1578

	1	-				
K	17.02	17.01	17	16	15	4
TATOT	25 Liter capacity water heater	10 Liter capacity-water heater	Providing and installation of stationary storage type Electric water heater (Geyser) of various sizes by means of Expansion-bolts with nuts and washers, including embedding of expansion-bolts in the wall, providing and fixing of Non-return valve, Dead weight safety valve, 2 No C.P. connection rods 18" long, making good the damages, electrical connections, safety valve connections, testing and commissioning etc. as required. Make:-Racold,Jaquar,Usha ;minimum 3-star rating.	S/F rubber mat 1x2 meter long 12mm thick infront of main panel as required including carriage of material with in all leads and lift.	S/F Shock treatment chart on the existing wall etc as required including carriage of material within all leads and lift.	Supplying and drawing Lan came Cat to solid cupper conductor 4 pair protected with PVC Shouthed in existing surface /recessed steel/PVC Conduit as required. Make :Polycab,Finolex ,D-link.
Contract of the last	3	50 to 2 grand		_	71	200
	10714	8338		2400	150	
	Rupees Terr thousand seven hundred fourteen only.	Rupees Eight thousand three hundred thirty eight only.		Rupees Two thousand four hundred only.	Rupees One hundred fifty only.	rupees runy seven only.
F 17	Each	Each		Each	Each	Melci
367907	32142	16676	0	2400	150	00000

Executive Engineer,
Electrical Division,
HPPWD Unn.

	Rupees Six hundred eight only.	608	Meter	5	2 X 6 sq. mm + 1 X 6 sq. mm earth wire	2.03
	Rupees Four hundred forty nine only.	449	Meter	ΙQ	2 X 4 sq. mm + 1 X 4 sq. mm earth wire	2.02
	Rupees three hundred thirty five only.	335	Meter	10	11 2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	2.01
Control of the Contro					Wiring for circuit/submain wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed steel conduit as required, Make: Plaza KEL Finolex or its equivalent as approved by Er-In-Charge	2
	Rupees One flourend eight handred.	1854	Each	30	H	
					Wiring for light point/ fan point/ exhaust fan point/ call hell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modularswitch, modular plate, suitable GI box and earthing the pointwith 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as reguired.Make :-Anchor (Roma classic),L&T (Entice), Legrand (Myrius) or its equivalent as approved by Er-In-Charge	
		4	70000	1		_
	In In words.	Rate In	Unit Unit	Owantity	Sr. Description Description Open Descrip	2
	Time Limit: Six months.		O 10 III			
	Earnest money:- Rs. 10,000/-					
	Estimated cost:- Rs. 4,99,290/-					
	Job No. 4				DRAFT SCHEDULE OF QUANTITY	

Supplying and fixing of LED 12 watt bulk head-fitting with all accessories including making connections, testing etc. as required: Make Make Panasonic, Wipro Philips or its equivalent as approved by Er-In-Charge(Five year warranty)	220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:- panasonic(Cat no PBLM 33124, Philips, wipro or its equivalent as approved by Engineer-in-Charge	Supplying and fixing recess LED cob light 12 watt, 4000k, (FYEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9. Harmonic Distortion<10%	Supplying and fixing recess LED square panel 2 X 2 36 watt, 6500k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9, Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:-pamasonic(Cat no PBLM 22367, Philips, wipro or its equivalent as approved by Engineer-in-Charge	Supplying and fixing suitable size GI box with modular plate and cover in FRLS on surface or in recess, including providing and fixing 6 pin 5/6 & 15/16 amps modular socket outlet and 15/16 amps modular switch, connection etc. as required.Make:-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Er-In-Charge
with alt 8	nections, o PBLM ngineer-in-	0k, (Five 22 n<10%	watt, 27 ompatible itable for all . Make:- uivalent as	plate and 1 ng and 115/16 :-Anchor uivalent as
Each		Each	Each	Each
822		1252	4701	628
Rupees Eight hundred twenty two only.		Rupees One thousand two hundred fifty two only.	Rupees Four thousand seven hundred one only.	Rupees Six hundred twenty eight only.
6576		27544	126927	628

	1			*		
m dise		10	9	∞	7.01	7
Providing, laying and fixing of interconnecting copper piping with Nitrile tublar insulation AC indoor to outdoor for split type AC 1.5 ton and 1.8 AC as required complete in all respect.	connection, light connection and net working connection including partition chip flexible cover end cap as required complete in all respect .Make:-Legrand ,MK	Supplying and fixing of DLP 105x50 mm PVC adaptable trunking on the exiting wall at required height from lower level for power	Providing and fixing 4.00 mm dia copper wire on surface or in recess for loop earthing as required.	Supplying and fixing extra down rod of 10 cm length G.l. pipe; 15 mm dia; heavy gauge including painting etc.as required.	10 watt	Providing and fixing of following type surface mounted Luminaire LED batten, having high Quality design aluminium extruded decorative end caps and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion>15% and efficiency> 100 Lumens per watt, CRI> 80 suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc as:Make Philips, Panasonic jaquar or its equivalent as approved by Er-In-Charge(Five year warranty)
70		75	130	30	ÇJ	
Meter		Meter	Meter	Each	Each	
1150		1174	155	46	363	i in the second
Rupees One thousand one hundred fiofty only.		Rupees One thousand one hundred seventy four only.	Rupees One hundred fifty five only.	Rupees Forty six only.	Rupees thee hundred sixty three only.	
80500		88050	20150	1380	1089	

And the same of the same

þ

1892	Rupees One thousand eight hundred ninety twoonly.	1892	Each	-	MCBDB 8 WAY Double Door	15.01
					Supplying and fixing following way, single pole and neutral, sheet sueal, MCB-distribution board, 340 V, on surface/recess, complete with tinned copper bus bar, neutral busbar, earth bar, din bar, interconnections, powder paintedincluding earthing etc. as required. (But withoutMCB/RCCB/Isolator)Make L&T, Schneider, ABB or its equivalent as per best satisfaction of Engineer-in -charge.	5
1195	Rupees One thousand one hundred ninety five only.	1195	Each	-	Supplying and erection of 40/50/63 amps, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of pole Double pole in the existing MCB DB complete with connections etc. as required:-Make L&T, Hager, ABB or its equivalent as approved by Engineer-in -charge.	I
1052	Rupees Two hundred sixty three only.	263	Each	4	single pois	13.01
- 27					Supplying and fixing 5 amps to 32 amps , 240/415 volts, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.) Make L&T, Hager, ABB or its equivalent as per best satisfaction of Engineer-in -charge.	=
20741	Rupees Two thousand nine hundred sixty three only.	2963	Each	7	Supplying and fixing of wall mounted 2U rack size; 550x400 mm depth including its complete accessories i.e. front glass door (tinted,toughened) with lock&key, 2 pairs pf 19" mounting rails with U-marking welded side walls 1U cable manager(1), hardware packet (1pkt), 3 socket 5 amp, power distribution unit (1 No) as per product code NWR-4U-5040-GR as required. Make:- D-Link.	5

	17.02	17.01	7	- 16
Total	25 Liter	10 litre	Providing and installation of stationary storage type Electric water heater (Geyser)of following capacity various sizes by means of expansion-bolts with nuts and washers, includingembedding of expansion-bolts in the wall, making good the damages, electrical connections, testing etc. complete as required:-Maker-Usha,Bajaj,Recold or its equivalent as per best satisfaction of Engineer-in -charge.	Earthing with copper earth plate 600 mm X 600 mm X 3 mm thick including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe of 2.7 metre long etc. with charcoal/ coke and salt as required.
	-	ы		2
	Each	Each		P/Set
	10714.00	8338		13838
	Rupees Ten thousand seven hundred fourteen only.	Rupees Eight thousand three hundred thirty eight		Rupees thirteen thousand eight hundred thirty eight only.
499290	10714	16676		27676

Executive Engineer, Electrical Division, HP.PWD., Unn.

		-1011				1	14	THE Y				_		_
			2.04	2.03	2.02	201	2		N y	Name of				
Canadia	Supplying & fixing suitable size Gl box wib modular plate and cover in front on surface or in recens the providing and fixing 25 amp modular socket outlet and 25 Amps modular SP MCB, "C" curve including connection, painting etc. as requiredMake :-Anchor (Roma classic), L&T(Entice), Legrand (Myrito) or its equivalent as approved by Er-In-	complying and arong a omparer boardarying is no can insolute these as measure, is no re- module snodular base & cover plate; 3 and 5 amp switched may 5 amp sockets; I may 15/16 amp switch. I no 15 amp mod socket including connections are as required Make >- Anchor (Roma classic.), L&T(Entice), Legrand (Myrius), or its equivalent as approved by Er-In-Charge.	2 × 10 sq. mm + 4 × 6 sq. mm carth wire*	4 X 4 sq. mm + 2 X 4 sq. mm carth wire	2 X 4 sq. mm + 1 X 4 sq. mm earth wine	2 X I 5 sq. mm + I X I 5 sq. mm earth wire	Wring for circuit submain weing alongwith earth wire with the following sizes of FRLS PYC intuitied copper conductor, single core cable in surface/ received PVC copduit as required Make-Plaza, XEL, Finolex & pvc conduit pipe AKG, BEC, Diplact Poly indic or its equivalent as approved by Er-In-Charge	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC inschaed copper conductor single core cable in surface / recessed heavy class PVC conduct, with modular switch, modular plate, suitable Gl box and earthing the point with 1.5 sq.mm, FRLS PVC insulated copper conductor single core cable etc is required.Make: -Anchor (Roma: classic.), L&T(Enrice), Legrand (Myrius): pvc conduit Dipliest, AKG, BEC, POLY India or its equivalent as approved by Er-In-Charge.	Description of Items	Name of works- Providing E.L. in the MDR Diagnostic Centre at Dr. RKGMC at Hamirpur Distr. Hamirpur (H.P).				DRAFT SCHEDULE OF QUANTITY
	N		10	10	*	30		п	Quantity	it. Hamirpur	e.i			
-	606	100	383	529	323	204		1229	fo fig.	(M.H)				
	Rupees six hundred six only.	twenty two only.	Rupees five hundred eighty three only.	Rupoes Five hundred twenty nine only.	Rupces these hundred twenty filtre	Ruptes Two hundred four only.		Rupees Che thausand two hundred twenty nine only.	In words.	The state of the s	Tiese Limit: Six months.	Farnesi money:- Rs. 3,100/-	Estimated cost:- Rs. 1,52,307/-	Job No. 65
	Each		Meter	Meter	Meter	Meter		Exch	Unit			The same	1	
1	1212		9082	5290	10011	6120	0	14748	Amount				N. Park	-

Each	m	Rupees Fourthousand seven hundred one only.	1701		Supplying and fixing recens LED square panel 2 X 2 feet 36 watt, 6500k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion<10% und efficacy>100 Luments per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, resting and commissioning etc. Make- parasonict Cat no PHLM 22367, Philips, wipro or its equivalent as approved by Engineer-in-Charge	8
3	7 18 18 18 18	Rupees Eight hundred fifty nine only.	859		Supplying and fixing excess round type LED, 35 watt, 6000k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > 9, Harmonist Distortion<10% and efficacy >100 Luments per want, suitable for input vultage: AC 220-240 V, 50/60H2, complete with all necessories, connections, resting and commissioning etc. Make:- Parasonic(PPAM1156 BS), Philips, wipro or its equivalent as approved by Engineer-in-Charge.	14.12
Each		eighty live only. Rupees Two thousand seven hundred Birty four only.	2754		Providing and Installation of Wall mounting fan of 400 mm sizes the hang the same in position on the wall, connections, testing land commissioning, etc.as, required with best satisfaction of Engineer is charge Make. Usha(MIST AIR DUSOS/ICY), Bajaj, Crompton or its equivalent as approved by Er-in-charge	00
Each	to	Rupees Two thousand eight hundred	2885	-	Ceiling fan 1200mm	7.01
	121	colon) and doub.			Providing, Installation, testing and commissioning of ceiling fan with modular type fan regulator, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 manning twisted flexible, conton braided, copper cable, including providing and fixing particular particular providing and fixing particular short cover on the fan box and earthing etc. as req uired. Make:	*
Each	-	Rupers Three thousand six hundred	3682		Exhaust Fant (ilicavy Duty).	6.01
				13	Providing and installation exhaust fan of fellowing sizes in the existing opening including making the hole to suit the size of the above fan, making good thedamages, connections, testing and commissioning etc. as required: Make:- UsharS JH TURBO HDEF 900 RPM J.Hajaj, Crampton or its equivalent as approved by E1-in-charge.	
Each		Rupees Six Insuized twenty eight only	628	14	Supplying and fixing suitable size (II low with modular plate and cover in FRLSeat on surface or in roces, including providing and fixing 6 pin 5/6 & 15/16 steps modular socker order and 15/16 steps modular switch, consection out in required MakeAnchor (Roma classic), L&TiEnticel, Legrand (Myrius) or its equivalent as approved by Er-In-Charge	-

- 一村は

	1	1 84		A HE	Allen	119		-	1:-
-	5	5	14.01	I	11	12.01	13	11.01	-
equivalent as approved by Er-in-charge	Providing and installation of stationary storage type Electric water heater (Geyser)of various sizes by means of expansion-bolts with nuts and washers, including-omboding of expansion-bolts in the wall, making good the damages, electricalconnections, testing etc. complete as required: Make:UshaiMETALLIC COLOUR 25 LABajaja;Recold or its	Supplying and fixing Aluminium bands LED 10 wait, 6500k, and it should be compatible with specification i.e. Power Factor > 9. Harmonic Distortion c10% and efficacy > 100 Lument per wait, suitable for input voltage: AC 120-240 V, 50400Hz, complete with all accessories, connections, testing and oparationisting etc. Make: Jaquar (Model -LGL/01X010XCyPhilips,Panasonnic or its equivalent as approved by Engineerin-Charge (Five YEAR WARRANTY)	40ansp. double pole, (single phase and neutral)	Supplying and fixing following rating, double pole, (single phase and neutral), 240 volts, residual current circuit breaker (RCCB), having a sensitivity current 30 mills amperes in the existing MCB DB complete with connections, testing and commissioning etc. as required. Make - parasonic(Cut no FBLM 22367/Philips, volpro or its equivalent as approved by Engineer-in-Charge.	Supplying and erection of 40/50/63 amps rating, 10 KA breaking capacity, 240 walts, 'Courves, miniature circuit breaker of following poles in the existing MCB DB complete wall connections see: as required:—Make:- parasonict Car no PBLM 22367.Philips://wiprofar its equivalent as approved by Engineer in Charge.	Single pole	Supplying and fixing 5 imps to 32 imps rating, 240/415 volts, 10 kA, "Convernitionize circuit breaker suitable for inductive had of following poles in the existing MCB DB occupies with connections, lesting and commissioning etc. in required. Make: pagespare Car no PHLM, 223/67, Philips, wapen or its expansion as approved by Engineerin-Change."	12 way, Dauble door	MCB destriction board, 240 vents, on surface/ recess, complete with timed copper has bit, neutral bus bit, earth hit, die bit, interconnections, powder painted including curthing etc. as required (But without MCB/RCCIM/Solator/Make;-L&T Cit. No. (CM/9/80170000AG),Legrand/Hagger , or its equivalent as approved by Engineer-in-charge. Make: panasonic! Cut no PBUM 22367.Philips, wapers or its equivalent as approved by Engineer-in-Charge.
	-					3		Ī	
, i	10714	416	2960		1186	263	MAR.	2423	
	Rupees Ten thousand seven hundred fourten only.	Rupees Four hundred sixteen only.	Ropocs Two thousand nine hundred stray only.		Rupees One thousand one hundred ninety five only.	Rupots Two hundred sixty three only.		Ruploes Two thousand four hundred menty three only.	
4	Each	Each	EACH		Each	Each		Each	
d	10714	416	2960		1195	1841		2423	

The state of

						1115	
	27	20.01	8	19	18.01	=	7
Total	Supplying and fixing 4 pole MCCB. Enclosure with all soccessories including connections, as required for DU1001t/DN0/1251t/	125 anij025 K.A	Providing and fixing following rating and brenking capacity MCCB with thermomagnetic release and remnital spreaders in existing cubicle panel board including drilling holes in cubicle panel, making competitors, etc. as require	Supplying and making end termination with brass conspecsion gland and copper gland fig. 25cme x120 squant. I like grade cablePVC insulated and PVC sheathed / aluminum cable of following size 3.5 core x120 sq mm.	Armouned cable 129 sq. min (3.5 core)	Providing & Laying of one number aluminium conductor, PVC insulated and PVC sheathed armoured/ XLPE power table, 1.1 KV grade of following sizes on wall surface as required Maker-KELPQLYCAR PLAZA or its equivalent as approved by Ersinscharge.	Providing and fixing 250 AMP, four pole, 415 with, Ch-Load change over switch in short steel Enclouser AC 23A duty, with side handle operation, including drilling holes on bound marking commections, etc. as required. Make-L&T, Legrand. Hagger, or its equivalent as approved by Engineer-in-change.
					12		191
Printer.	1943	12222		100	1208		22283
	Rupers One thousand nine hundred forty three only.	Rupoes Twelve thousand two hundred discrety two only.		Rupoes three hundred one only.	Rupees One theatsand two lundred eight only.		Rupees Rwwnry two thousand two bundred eight three only.
	Each	Each		5	Each	16	Each
152307	1943	12222	0	1204	14496	a	22283

Executive Engineer, Elegarical Division, HP-PWD., Una.

Executive Engineer,
District Division,
HP.PWD., Unn.

272697	The second secon	1		200	ТОТАL	
6000	Rupees One thousand five hundred only.	1500	Each		Reinstallation all type of air coriditioner indoor and outdoor unit complete in all respect as required	00
CONC	supers one mousand live hundred only.	- Joue	Taken		all respect as required	
14928	Rupees One thousand two hundred forty four only.	1244	Meler	12	Providing, laying and fixing of interconnecting copper piping with Nitrile tublar insulation AC indoor to outdoor for split type AC 1.5 ton and 1.8 AC as required complete in all respect.	0
27000	Rupees One thousand three hundred fifty only.	1350	Meter	20	Supplying and fixing of DLP 105x50 mmPVC adaptable trunking on the exiting wall at required height from lower level for power connection, light connection and net working connection including partition chip flexible cover end cap .Make:-Legrand ,MK or its equivalent as required complete in all respect.	u
2370	Rupees One hundred fifty eight only.	158	Meter	15	Supplying and drawing copper conductor 3 core 2.5 Squan industrial cables & PVC insulated, PVC round sheathed multicore industrial Cables as required complete in all respect.	
2370	Rupees Seventy nine only.	79	Meter	30	20 mm	3.01
0					Supplying and fixing of 20 mm of medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required.Diplass/BEC/ Polyfit.or its equivalent as approved by Er-In-Charge	u

Executive Engineer, Electrical Division, HPPWD Una.

DRAFT SCHEDULE OF QUANTITY

Job No. 08

Estimated cost:- Rs. 4,08,381/-

Earnest money:- Rs. 8,200/.

Time Limit: One year,

3.02	3.01	u	2	10.00	1.02	1.01		No.
5 pin 5/6 amp socket outlet	5/6 amp Modular switch	Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required	Wiring for twin control light point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface I recessed steel conduit, 2 way modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required. Make :-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Engineer-In-Charge		Group C	Group A	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modularswitch, modular plate, suitable GI box and earthing the pointwith 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.Make:-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Engineer-In-Charge	Description of Items
00	∞		10		29	25		Quantity
122	76	3	1977	The state of the s	1854	1344		Fig.
Rupees One hundred twenty two only.	Rupees Sevenry six only.		Rupees One thousand nine hundred seventy seven only.	fifty four only.	Rupees One thousand eight hundred	Rupees One thousand three hundred forty four only.		In in words.
Each	Each	1	Each	-	Each	Each		UBIE
976	608	0	19770		53766	33600		Amount

40200	Meter	Rupees three hundred thirty five only.	335	120	2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	8.01
0					Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed steel conduit as required Make:-Plaza,KEI,Finolex or its equivalent as approved by Er- In-Charge	
					sheet cover for each 2 module metal box, one no computer jack (RJ-45)with shutter including connections etc as requiredMake :-Anchor (Roma classic).L&T(Entice),Legrand(Myrius) or its equivalent as approved by Engineer-In-Charge	
4374	Each	Rupees One thousand four hundred fifty eight only.	1458	AN HAR SHOUL		7
1470	Each	Rupees Seven hundred thirty five only.	735	2	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 2 nos. 3 pin 5/6 amps modular socket outlets and 2 nos 5/6 amps modular switches, connection etc. as required. .Make :-Anchor (Roma classic).L&T(Entice),Legrand(Myrius) or its equivalent as approved by Engineer-In-Charge	6
6908	Each	Rupees Six hundred twenty eight only.	628	=	Supplying and fixing suitable size GI box with modular plate and cover in FRLSont on surface or in recess, including providing and fixing 6 pin 5/6 & 15/16 amps modular socket outlet and 15/16 amps modular switch, connection etc. as required. Make :-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Engineer-In-Charge	v.
6118	Each	Rupees four hundred thirty seven only.	437	14	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 3 pin 5/6 amps modular socket outlet and 5/6 amps modular switch, connection etc. as required. Make :-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Er-In-Charge	

		中国国际的目		3						
5	12.01		11.01	=	10	10.6	9	8.04	8.03	8.02
Providing and installation exhaust fan of following sizes in the existing opening,including making the hole to suit the size of the above fan, making good thedamages, connections, testing and commissioning etc. as required: Make:-Usha(AEROCLEAN PLUS DBB),Bajaj,Crompton or its equivalent as approved by Engineer-in-charge	Ceiling Fan 1200 mm sweep	Providing, Installation, testing and commissioning of ceiling fan without regulator, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mmtwin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and garthing etc. as req uired: Make: Usha(TECHNIX PLUS), Bajaj, Crompton or its equivalent as approved by Engineer-in-charge	25 mm.	Supplying and fixing of following sizes of PVC conduit along with accessories insurface/recess including painting in case of surface conduit, or cutting the walland making good the same in case of recessed conduit as required.	Supplying and drawing of UTP 4 pair CAT 6 LAN cable in the existing surface/recessed steel/PVC conduit as required.	3x1,5Sq.mm + 1x1.5sq./mm earth wire.	Supplying and drawing of following sizes of FRLS PVC insulated copper conductor, single core Cable in the existing surface/recessed steel/ PVC conduit as required.	2 X 10 sq. mm + 1 X 6 sq. mm earth wire	4 X 4 sq. mm + 2 X 4 sq. mm earth wire	2 X 4 sq. mm + J X 4 sq. mm earth wire
	06		30		36	30		9	48	100
The said	2789		113		S	97		730	714	449
The state of the s	Rupees Two thousand seven hundred eighty nine only.		Rupees One hundred thirteen only.		Rupees fifty three only.	Rupees ninety seven only.		Rupees Seven hundred thirty only.	Rupees Seven hundred fourteen only.	Rupees Four hundred forty nine only.
1	Each		Meter		Meter	Meter		Meter	Meter	Meter
0	22312	0	3390	0	1908	2910	0	6570	34272	44900

- 1 P 1021	ARBITE TOP	Balin				•
-18		-17	16	2	E	13.01
Supplying and fixing surface round / square type LED 15 watt, 6000k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9, Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:- Panasonic (Model -PDLM10156BR)/Philips, wipro or its equivalent as approved by Engineer-in-Charge	bolts with nuts and washers, includingembedding of expansion- bolts in the wall, making good the damages, electricalconnections, testing etc. complete as required:-Make:- Usha(Model Mist 6 litre).Bajaj,Recold or its equivalent as approved by Engineer-in-charge	Providing and installation of stationary storage type Electric water heater (Geyser)of various sizes by means of expansion-	Providing and installation of stationary storage type Electric water heater (Geyser) of various sizes by means of expansion-bolts with nuts and washers, including embedding of expansion bolts in the wall, making good the damages, electricalconnections, testing etc. complete as required:-Make:-Usha(Model Mist 25 litre), Bajaj, Recold or its equivalent as approved by Er-in-charge	S/F louver and shutter for 300mm/350 mm on 12mm thick ply board as required complete inal respect	Providing and installation exhaust fan of 250mm (Plastic body) size in the existing opening,including making the hole to suit the size of the above fan, making good thedamages, connections, testing and commissioning etc. as required: Make:- Usha,Bajaj,Crompton or its equivalent as approved by Engineer-in-charge	Exhaust Fan, Light duty, 300 mm sweep
		-		-	2	1
1136		6754	9970	600	1871	2,902
Rupees One thousand one hundred thirty six only.		Rupees Six thousand seven hundred fifty four only	Rupees Nine thousand nine hundred seventy only.	Rupees six hundred only.		sixty two only.
Each		Each	Each	Each	Each	Eacn
20448		6754	9970	600	3742	2302

_				Language and the second	
	22	Decree	21	120	75
	Supplying and fixing of bulk head fitting LED-12 watt .6500k. (Five YEAR WARRANTY) and it should be compatible with specification e.i. Power Factor > .9.Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.Make-Jaquar (Model-)/Jaquar/PHILIPS_Panasonic or its equivalent as approved by Engineer-in-Charge	specification-i.e. Power Factor > 9. Harmonic Distortion<10% and efficacy > 100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make: Jaquar/Philips, Panasonnic or its equivalent as approved by Engineer-in-Charge	Supplying and fixing Aluminium batten LED 10 watt, 6000k,	Supplying and fixing SURFACE 1x4 36 WATT LED , 5700k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, compections, testing and commissioning etc. Make:- panasonic (Model -PBTM17228)/Phillips. Wipro or its equivalent as approved_by Engineer-in-Charge	Supplying and fixing Aluminium batten LED 24 watt, 6000k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > .9, Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:-Jaquar (Cat No LGLZ01X024XN)Philips,Panasonnic or its equivalent as approved by Engineer-in-Charge
			3	12	00
	822		363	4299	595
	Rupees Eight hundred twenty two only.		Rupees three hundred sixty three only.	Rupees Four thousand two hundred ninety nine only.	Rupees five hundred ninety five only.
	Each		Each	Each	Exc
	2466		1089	8598	4760

¥.

28	1	2	20	71	DE COL		24		
- 4	27	26.02	26.01		26	25	24.01	22	t
Supplying and fixing true power make advanced as system having copper pipe 2 meter long 50 mm disterminal size 50x6 mm, internal strip size 25x2 with compound including exvation of pit and refilling the san making earthing pit cover 13 inch dia as required compall respect, make: True power, Earth pius, Ashloka equivalent as per best satisfaction of Engineer-in-charge.	Supplying and fixing PVC connection etc. as required.	16 way Double door	12 way, Double door	CB/Isolator	Supplying and fixing of MCI surface/ recess, complete wi bus bar, earth bar, din bar, including earthing etc.	Supplying and fixing 5 amps 10 kA, "C" curve,miniate inductive load of following complete with connections, required.	40ump, double pole, (single phase and neutral)	Supplying and fixing following phase and neutrally, 240 volts, (RCCB), having a sensitivity existing MCB DB complete comunissioning etc. as required	breaking capacity, 240 volts, 'C breaker of following poles in the with connections etc. as required:-
Supplying and fixing true power make advanced earthing system having copper pipe 2 meter long 50 mm dia with terminal size 50x6 mm, internal strip size 25x2 with 50 Kg compound including exvation of pit and refiling the same and making earthing pit cover 13 inch dia as required complete in all respect, make: True power Earth plus, Ashloka or its equivalent as per best satisfaction of Engineer-in -charge.	batten/ angle holder including	and the property of the control of	The second second second second		Supplying and fixing of MCB distribution board, 240 volts, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.	phase and neutral)	Supplying and fixing following rating, double pole, (single phase and neutral), 240 volts, residual current circuit breaker (RCCB), having a sensitivity current 30 milli amperes in the existing MCB DB complete with connections, testing and comunissioning etc. as required.	breaking capacity, 240 volts, 'C curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-
13	7	- Land	914		ja i	17	2		
13144	59	2805	2257	1		263	2960		
Rupees thirteen thousand one hundred forty four only.	Rupees fifty nine only.	Rupees Two thousand eight hundred five only.	Rupees Two thousand two hundred fifty seven only.			Rupees Two hundred sixty three only.	Rupees Two thousand nine hundred sixty only.		ninety five only.
Each	Each	Each	Each			Each	Each		į
26288	413	2805	2257	200	0	4471	5920	0	14

	and the second second	
	S.	29
TOTAL	Supplying and fixing street light LED 60 watt with G.I bracket die cast Aluminium housing with frame and toughened glass, pipe mounting 5700k, (Five YEAR WARRANTY) and it should be compatible with specification e.i. Power Factor > .9, Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make - Jaquar (Model -LSRT015060XW)Philips/wipro or its equivalent as approved by Engineer-in-Charge	Supplying and laying 8 SWG copper, wire at 0.50 metre below ground level for conductor earth electrode, including connection/ termination with GI thimble etc. as required
	u	30
	5212	112
	Rupees Five thousand two hundred twelve only.	Rupees One hundred twelve only.
	Each	Meler
408381	15636	3360

Executive Engineer, Electrical Division, HPPWD Una.

DRAFT SCHEDULE OF QUANTITY

Job No. 17 Estimated cost:- Rs. 4,47,161/-Earnest money:- Rs. 9,000/-

NAME	s at Govt.S.S.S.Singan, Tehsil Haroli, D	istt.Una (HP) (SH:	-Providing E .l.there in)	Tab	Amount
S. No.	Description	Quantity Rate In	Rate In	In Words.	Unit	Amount
-	Wiring for light point / fan point / exhaust fan / call bell point with 1.5 Sq. num. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required. (Finolex, KEL, Anchor, L&T make)		3			1 1 1
1.01	Group C.	102	1653	Rupees One thousand six hundred fifty three only.	Each	168606
2	Wiring for twin control light point with 1.5 Sq. mm. PVC insulated heat resistant, flame retardant (HRFR) and low amoke single core (flexible)	100				N.
	copper-conductor cable in surface/recessed steel conduit with 2-way, 5/6 amps, plano type switch and earthing the light point with 1.5 Sq.mm, HRFRLS/PVC insufated single core copper conductor cable as required.(Finolex,KELAnchor,L&T make)					
2.01	Group C	4	9161	Rupers One thousand nine hundred sixteen only	Each	1997
3	Wiring for light plug with 2x1.5 Sq. runt. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/ recessed steel conduit along with 1 No.1.5 Sq.rum. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make)	. 88	277	Rupees Two hundred seventy seven only.	P/mir,	23545

9.01 Single p	9 Supplyin capacity in the ex	as requir	7 Supplyin size) on the front amps, pi	6.02 S pin S/	6.01 S.P. 5/6	6 Supplyin	5.01 3x1.5 Sq. mm.	5 Supplyir flame re conducte required	4.01 2x1.5 Sq. mm	conductor No.HRFRI for earthin
Single pole, Car-A.	Supplying and erection of 6 amps. to 32 amps. rating, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-	Supplying and fixing bakelite batter/angle holder including connections etc. as required: (SSK,Anchor make)	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, piano type switch, connections, painting etc. as required.	5 pin 5/ 6 Amps socket outlet, porcelain base/ piano type.	S.P. 5/ 6 Amps one way switch, piano type.	Supplying and fixing following rating Piano-type switch /socket on the existing switch box / cover including connections etc. as required.	t, min.	Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cuble in existing surface / recessed, Steel/PVC conduit as required.(Finolex,KEI,Anchor,L&T make)	1-mm.	conductor cable in surface/recessed steel conduit along with I No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Finolex,KEI,Anchor,L&T make)
12		17	6	6	6		170	0	130	
243		92	269	71	49		82		277	
Rupees Two hundred forty three		Rupees Ninety two only.	Rupees Two hundred sixty nine only.	Rupees Seventy one only.	Rupees Forty nine only.		Rupees Eighty two only.		Rupees Two hundred seventy seven only.	
Each		Each	Each	Each	Each		P/mtr.	124	P/mtr.	
2916		1564	1614	426	294	N/L	13940	4	36010	1991

A STATE OF THE PARTY OF THE PAR	The state of	A101201020							
15	14	The state of the s	13	12.01	12	10.11	- =	10.01	ā
Supplying and laying 6 SWG-G.L. wire at 0.50 mtr. below ground level for earth electrode conductor, including soldering etc. as required.	Extra for using salt and charcoal for pipe earth electrode complete as required.	and salt) complete as required.	Earthing with GI earth pipe 4.5 mtr. long and 40mm dia, including accessories and providing masonry enclosure with cover plate having	Double door-16 way	Supplying and fixing of following way, single pole and neutral sheet steel MCB distribution board, 240 volts, on surface / recess, complete with tinned copper bus- bar, wire-set, neutral link, earth bar, din-bar, detachable gland plate, blanking plate, cable, identification labels interconnections, phosphatized and powder painted, including earthing etc. as required:-	40 Amps. Cat-A.	Supplying and fixing following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB), having a sensitivity current up to 300 miliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required.	Double pole, Cat-A.	240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-
40			-		i i	-		-	
38	1613		3351	2691		2820		Ξ	
Rupees thirty eight only.	Rupees One thousand six hundred thirteen only.		Rupees three thousand three hundred fifty one only.	Rupees Two thousand six hundred ninety one only.		Rupees Two thousand eight hundred twenty only.		Rupees One thousand one hundred eleven only.	
P/mtr.	P/set		P/set	Each		Each		Each	
1520	1613	a disease y con	3351	2691		2820		1111	- 5

11		20	19	=	17	16.0	5
(Wipro LR02-291-XXX-57-XX/Clair/Philips make)	K,CRI 80,IP rating 66, up to 10KVA electric surge protection and bracket of steel conduit pipe 32 mm., complete with all accessories connections tecting and commissioning are as required.	115	Providing and fixing LED surface/pendent mounting Tube fixture 24 watts Jaqour make glazed LED batten Cat No.LGLZ01X024XN high quality design aluminium extruded decorative end caps as per best satisfaction of Engineer-in-Charge complete as required.	Supplying and fixing Step type fan regulator (Socket type) 100 watts on the existing switch box/cover complete making connections etc.as required.(SSK/Anchor or its equivalent make)	17 Supplying and fixing Fan box of M.S.sheet with iron rod book 12 mm.in place of junction box complete as required.	16.01 Ceiling Fan 1200 mm sweep, Category-A	Providing, Installation, testing and commissioning of ceiling fan without step type fan regulator modular, air delivery 215 m3 /min power input 30 watts speed 330 RPM, including wiring the down rods of standard length (up to 30 cm) with 16/0,20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and carthing etc. as required: (Usha-Technixplus BEE 3 Star rated model) or in equivalent make)
	2	s ng	ality 48	on the 30 etc,as	ILis 30	30	eg er G
5 1		3508	831	462	A	2814	
		Rupees three thousand five hundred eight only.	Rupees Eight hundred thirty one only.	Rupees four hundred sixty two only.	Rupees forty two only.	Rupees two thousand eight hundred fourteen only.	
		Each	Each	Each	Each	Each	
		31572	39888	13860	1260	84420	

Transmitted and the second

大社の日本の一大社の大学

Total Control

	22.01	22	21
Total:-	22.01 16 sq.mm.Twin core	Wiring for sub main wiring with following sizes of weather proof twin core aluminium conductor cable on G.I. bearer wire etc. as required.	Supplying and fixing LED Lamp 9 wants 6500 K E-27,900 Lumens 240 volts AC-supply 50 HZ in the existing batten holder, pendent holder, wall bracker & bulk head fitting etc. as required (Tisya cat. No.AL946611X/Panasonie/Philips make)
	35		17
	67		243
	Rupees sixty seven only.		Rupees Two hundred forty thre only.
	P/mtr.		Each
447161	2345		4

Executive Engineer, Electrical Division, HP.PWD.,Una.

						Examine periodically all safty devices and governor and all	1.03
THE PERSON NAMED IN	1	STORES IN	1	15	1	Charles of the think of the same	
						way.	
		- 1		ļ		overweight guide shows including rollers or gibs, interlock on Hoist	
0						button limit switches, Governor tension sheaves asseembly,	
-	Salahara Salahara	Section and Persons	1	1	of the same	counter weight and counterweight guide mils and buffers, top and	1
- Control	The State of the last	The state of the s			-	half lanterns, car direction indicators and all other car and landings	Ą
-	The state of the s	No. of Concession, Name of Street, or other Persons, Name of Street, or ot	Children			jaws, et and hall mechanical button, car and hall position indicators	400
S. Sandania			A Collision	1		Governor, governor sheave, shaft assembly bearings and Governors	
					-	selector tapes and mechanical and electrical driving equipment	ŧ
						rt. b3 transducers, resistance, condenders, power amplitter, transformers, contract, leads, dashpots timing devices. Steel	8
Annual Part Steel or water	Assert Males and Colored	-	10 10		- Control	sciedor leveling, devices cami, religis, solid state comonents e.g.	1
	THE PERSON NAMED IN		1	7 1 20		circuit, magnet frames and other mechanical parts, controller,	
		1				brush holdder, bearings, coils, registance for operating and Motor	E
						generator, Motor windings, rotating elements, commutator, brushes	
						contract, linings and components, Motor generator, motor, Motor	
						gear, Thrust bearings Drives sheaves, Drive shelves bearings, brake	200
-						Synstematic examining and adjustment of following machine, worn	102
		V				conductor cables and hoist way and machine room elevator wiring,	
					•	Renew all wires ropes and chain to mainteain an adequate factor of safety, to equalic tension on all hoisting ropes, repair or replace	10.1
			Γ				
						of parts as detailed below:-	
				- 7		Regular examination, lubrication and Adjustment of the equipment	1.00
			fig.	The same			No.
Amount		In In words.	Rate I	Unit	Quantity	Description	90
stt.	lift (Johnson make) in the ADR centre Hamirpur Distt.	ake) in the ADI	ohason m		No. Passeng	Name of Work:- Annual Comprehensive Muintenance contract (AMC) of INo. Passengers Hamirpur HP (For the period 10.09.2022 to 09.09.2023).	me of mirpu
1	One Year	Time Limit: One Year					
	Earnest money:- Rs. 2,000/-	Earnest mone					
1000	Esrtimted cost:- Rs. 99,710/-	Escrimted cos			100		
	Job No. 18	111				DRAFT SCHEDULE OF QUANTITY	

	3.1	
	1,05	1.04
::IVIOL	(Machine No. L-M1470	The firm will provide emergency minor adjustment all back services 24 hours as all working days as well as holidays! Sunday. The firm will maintain the lift in reliable and efficient operating connections.
	1.00	-Mi
	Job	
	99710	
	Rupees Ninety nine thousand seven hundred ten only.	
99710	99710	4.00

Executive Engineer, Electrical Division, HP-PWD., Una.

	DRAFT SCHEDULE OF QUANTITY	7			Job N	Job No. 19
					Estimated cost:- Rs. 2,14,288/-	25. 2,14,288/-
					Earnest money:- Rs. 4,300/-	Rs. 4,300/-
					Time Limit: One year.	year.
Name of V	Name of Work:- Annual Comprehensive Maintenance contract (AMC) of INos. Passenger lift (Johnson make) in Dr. RKGMC Hamirpur Distt Hamirpur HP. (For the year 2023-2024).	ios. Passeng	er HR (J	ohnson	make) in Dr. RKGMC 1	Hamirpur Distt Ham
No.	Description	Quantity	Unit	Rate	In In words.	Amount
1.00	Regular examination, lubrication and Adjustment of the equipment and planned maintenance in the systematic manner and replacement of parts as detailed below:-		41			
10.1	Renew all wires ropes and chain to mainteain an adequate factor of safety, to equalic tension on all hoisting ropes, repair or replace conductor cables and hoist way and machine room elevator wiring,			1	jes.	
1.02	Syustefiatic examining and adjustment of following machine, worn gear. Thrust bearings Drives sheaves, Drive shelves bearings, brake contract, linings and components, Motor generator, motor, Motor generator, Motor windings, rotating elements, commutator, brushes brush holdder, bearings, coils, registance for operating and Motor circuit, magnet frames and other mechanical parts, controller, selector leveling, devices cams, relays, solid state comonents e.g. PCB's transducers, resistance; condensers, power amplifier, transformers, contract, leads, dashpots timing devices. Steel selector tapes and mechanical and electrical driving equipment Governor, governor sheave, shaft assembly bearings and Governors Jaws, or and hall mechanical button, car and hall position indicators hall lanterns, car direction indicators and all other car and landings as installed by Johnson. Deflector or secondary sheave, bearing, car counter weight and counterweight guide raits and buffers, top and button limit switches, Governor tension sheaves assembly, compensating sheaves assembly car, counter weight and counter overweight guide shows including rollers or gibs, interlock on Hoist way.			一种种技术 的		

70	1.05 (Machine No. LJ6797	1.04 The firm will provide emergency 24 hours as all working days as will maintain the lift in reliable a
TOTAL:	OF THE PARTY OF TH	The firm will provide emergency minor adjustment all back services - 24 hours as all working days as well as holidays/ Sunday. The firm will maintain the lift in reliable and efficient operating connections.
	.00	
	Job	
-	214288	
	Rupees TwoLac. Fourteen thousand two hundred eighty eight only.	
214288	214288	

Executive Engineer, Electrical Division, HP.PWD., Una.

7			
			D.
			RAFT SCHED
			DRAFT SCHEDULE OF QUANTITY
	CHARGO.		YIII
	2		
	100		
Tim	Ear	Esrt	
e Limit:- One	nest money:-	imted cost:- I	Job
year.	Rs. 2,900/-	ds. 1,45,848/-	Job No. 20
			Į.
	Time Limit:- One year.	Time Limit:- One year.	Esrtimted cost:- Rs. 1,45,848/- Earnest money:- Rs. 2,900/- Time Limit:- One year.

brush I circuit selecto PCB's transfo selecto Govern jaws, c hall la as insti counte button compe overwa	brush I circuit selecto PCB's transfe selecte Goven	brush I circuit selecte		1.02 Syuste gear, 1 contra	1.01 Renew safety, condu	ŏ	No.	HP (for One y			
	hall lanterns, car direction indicators and all other car and landings as installed by Johnson. Deflector or secondary sheave, bearing, car counter weight and counterweight guide rails and buffers, top and button limit switches, Governor tension sheaves assembly, compensating sheaves assembly car, counter weight and counter overweight guide shows including rollers or gibs, interlock on Hoist way.	transformers, resistance, condensers, power amputter, transformers, contract, leads, dashpots timing devices, Steel selector tapes and mechanical and electrical driving equipment Governor, governor sheave, shaft assembly bearings and Governors jaws, or and hall mechanical button, car and hall position indicators	brush holdder, bearings, coils, registance for operating and Motor circuit, magnet frames and other mechanical parts, controller, selector leveling, devices cams, relays, solid state comonents e.g.	Syustematic examining and adjustment of following machine, worn gear, Thrust bearings Drives sheaves, Drive shelves bearings, brake contract, linings and components, Motor generator, motor, Motor generator, Motor windings, rotating elements, commutator, brushes	Renew all wires ropes and chain to mainteain an adequate factor of safety, to equalie tension on all hoisting ropes, repair or replace conductor cables and hoist way and machine room elevator wiring.	1.00 Regular examination, lubrication and Adjustment of the equipment and planned maintenance in the systematic manner and replacement of parts as detailed below;-	Description	Name of Work:- Annual Comprehensive Maintenance contract (AMC) of tNos. 13 Passenger HP (for One year from awarded date)			
	d all other car and landings condary sheave, bearing, car rails and buffers, top and sheaves asseembly, unter weight and counter s or gibs, interlock on Hoist	iming devices, Steel irical driving equipment bly bearings and Governors and hall posiiton indicators	e for operating and Motor nical parts, controller, solid state comonents e.g	of following machine, worn rive shelves bearings, brake r generator, motor, Motor ments, commutator, brushes	nteain an adequate factor of ropes, repair or replace chine room elevator wiring,	djustment of the equipment atic manner and replacement		ntenance contract (AMC) o			
							Quantity	f 1Nos. 13		3	
NT.							Unit	Passenger			
				1			Rate In				
				THE SECTION OF THE SE			In words.	lift (Johnson make) in Mini Sectt. Bhoranj	Time Limit: One year.	Earnest money:- Rs. 2,900/-	Cal diffical coat Wat 1980/040
										-/00/-	O-10404-
					,		Amount	Distt Hamirpur			

					TOTAL:	
_	Rupees One Lac. Forty five thousand eight hundred eight only.	145848	Job	1.00	1.05 (Machine No. L-J2337).	1.05
					1.04 The firm will provide emergency minor adjustment all back services 24 hours as all working days as well as holidays/ Sunday. The firm will maintain the lift in reliable and efficient operating connections.	1.04
-				-25	1.03 Examine periodically all safty devices and governor and all customary safty test.	1.03

Executive Engineer, Electrical Division, HP.PWD., Una.

1105	Each	Rugees One thousand one hundred five only.	1103	1	63 Araps. Cat-A	10.02
2210	Each	Rupoes One thousand one hundred five only.	5011	5.	40 Amps. Cat-A:	10.01
0					Supplying and crecion of 40.5083 augustaing, 10 KA treaking capacity, 240 volts. C curves, miniature circuit breaker of following poles in the existing MCB OB complete with connections etc. as required. Make L&T, Legrand Jiegar as approved by Engineer-in -charge.	10
ברונ	Each	Ripces Two haidred fifty two only	252	11	Single pole 16 Amp Cut-A.	9.02
1512	Each	Rupees Two hundred fifty two only.	252	0	Single pole 6 Amp Cal-A	10.5
					complying and mang 2 to 52.4 cating, artest 5 t, 10 kA, 12 cares, minimized circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required Make 1.6.1. Legrand Hegar es approved by Engineer-ta -charge	
3476	Each	Rupoes three hundred sixteen only.	316	=	Supplying and fixing metal box of 180mm X-100mm X-60mm deep (nominal size) on surface or in recess with suitable size of phenolic laminated sheet cover in FRLSont including providing and fixing 6 pin 5/6 & 15/16 amps socket outlet and 15/16 amps pixno type switch, connection, painting etc. as required. LegrandOdyrius).1.&T(entice). Anchor (Roma plus.) as approved by Engineer-in-charge.	-
1260	Each	Rupees Two hundrest ten only.	210	0-	Supplying and fixing metal box of 150mm X 75mm X 60mm deep (nominal size) on surface or in recess with suitable size of phenolic laminated sheet cover in FRLSont including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps pinno type switch, connection, painting etc. as required. (For light plugs to be used in non residential buildings) Legrand(Myrins), L&T(entice). Another (Roma plus.) as approved by Engineer-in -charge.	7
492	Each	Rupees eighty two only.	82	6	3 pin 5/6 A socket outlet	6.02
174	Each	Rupees Twenty time only,	29	6	S/6 amps switch	6.01
0					Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required.	6
4850	pinur	acupeus reinchy seven only.	16	3		*****

- 1				0 147	49			_	_				
-11	=	1502	1651		13	74	13	12.02	12.01	13	11.02	11.01	
EXHAUST Fan Light duty 300 mm sweep	Providing and installation exhaust fan of 300 mm sizes in the existing opering including making the hole to suit the size of the above fan, making good thedamages, connections, teating and commissioning etc. as required: Maker-Usha, Bajuj, Crompton or as approved by Er-in-charge	Ceiling Fan 1400 mm sweep	Ceiling Fan 1200 nm sweep	phenolic laminated sheet cover; on the fae hox and carthing etc. as required. Usha Tech-plus: Bajaj ultuma, Havell velocity not less than three area as approved by Er-in-charge. Usha Tech plus. Bajaj ultima, Havell velocity not less than three star as approved by Er-in-charge.	Previding, Installation, acting and commissioning of ceiling fan with regulator, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mm twin twisted flexible, conton braided, copper cable, including providing and fixing	Supplying and fixing LED Lump 9 watts E-27 base in the existing batton holder/pendent holder.	Supplying and fixing PVC batters/ angle holder including connections etc. as required.	12 way , Double door	8 way . Double door	MCB distribution board, 240 volts, on surface/ recess, complete with timed copper bus bar, neutral bus har, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator Make L&T, Legrand/Regar as approved by Engineer-in -charge.)	63 A	40 A	supplying and riving bottowing rating, doubte pole, (single phase and neutral), 240 with, residual current circuit breaker (RCCB), having a sensitivity current 30 milli amperes in the existing MCB DB complete with connections, testing and commissioning etc. as required. Make L&T, Legrand. Hegan as approved by Engineerin scharge.
1	1	1	K			9	9	1	2		-	2	
2285		2474	2895	M.M.		190	47	2257	1892		3373	2716	
Rupees Two thousand too hundred eighty five only.		Rupees Two thousand four hundred seventy four only	Rupees Two thousand eight hundred ninety five only.		12. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14	Rupees One hundred ninety only.	Rupees Forty seven only.	Rupees Two thousand two hundred fifty seven only	Rupees One thousand eight hundred ninety two only.		Rupees three thousand three hundred seventy three only.	Rupees Two thousand seven hundred sixteen only.	
Each		Each	Each			Each	Each	Each	Each		Each	Each	-649
9140	0	2424	17370		0	1710	423	2257	3784		3373	5432	0

2		. 13	21:01	21	20	19	ä
Providing and fixing following rating and breaking capacity MCCB with themomagnetic release and terminal spreaders in existing exhicle panel board including deiling heles in cobicle panel, making connections, etc. as require blake. L&T Cut. No. (CM97919GOHZOG),Legrand, Hagger , as approved by Engineer-in-charge.	indeplying and itsing interchight LEE-2 was with the tracks of Cita. Authorities because with frame and outliered plans, pipe mounting \$700k, (Five YEAR WARRANTY) and it should be compatible with specification cit. Power Factor > 9. Harmonic Distortion—10% and efficacy >100 Lumens per wait, nuitable for input voltage. AC 220-240 V. 50/60Hz, complete with all accessories, connections, using and commissioning etc. Make - Jaquar (Model -LPCRSRT25WLC)/Philips/wipro or its equivalent as approved by Engineer-in-Charge.	Supplying and fixing Deng dong bell suitable for single phase; 230 volts, complete as required.	TED Hazen Dight 10W(miner light)	Providing and installation of following type of LED bases with five year warranty aluminium housing anti-glare polycarbonate diffuser and energy efficient constant current, integralelectronic driver; suitable for input voltage: AC 220240 V, 50/60Hz, complete withall accentories, including mounting clamps, connections, testing etc. as required Made Wigno code (LL20-111-xxx-65 NE3*), Philips, Pantitionic as approved by Engineer-in-Charge.	Supplying and fixing surface round type LED 12 want, 6500k, (Five YEAR WARRANTY) and it should be compatible with specification (e. Power Factor > 9, Harmonic Distortion (10% and efficacy > 100 Lumens per want, suitable for input voltage: AC 229-240 V, 56360Hz, complete with all accessories, competions, testing and commissioning etc. Make: Pantasonic (Model -PDLM10206BR)Philips, suproof its equivalent as approved by Engineer-in-Charge	Supplying and fixing. Aluminium batters LED 20 want, 6000k, and it should be compatible with specification i.e. Power Factor > 9. Harmonic Descentive 10% and efficacy >100 Luminus per wait, suitable for input voltage. AC 220-240 V, 50/60Hz, complete with all successories, connections, testing and commissioning etc. Maker-parasonic (Model -PHTM18203) /Philips.Jaquar or its equivalent as approved by Engineer-ta-Charge (Fire YEAR WARRANTY)	Supply and fixing exhaust fan lower shutter for 300/300mm exhaust fan on the existing wall pointing including 12 mm thick wooden ply bound for suitable size of exhaust fan hole.
	1-11-11-11			4	500	5	4
	4.70	224	571	3	897	452	500
	Hilly only.	and the second of	Rupees Five hundred seventy one only.		Rupees Eight hundred thirty seven only.	Rappees four hundred fifty two only.	Rapees five hundred ninety three staly.
3		2.57.1	Each		Each	Each	Each
0	. COVE	998	2855	۰	6696	S#76	ממ

	2%	23	26	ĸ	24.01
TOTAL	Supplying and fixing 4 pole MCCB Enclosure with all accessories including connections, . as required	Providing and fixing 8 SWG dia copper, wire on surface or in recess for loop earthing as required.	Earthing with Earth pipe 4.5 mir long ,140 mm dsa, including accessories and providing 140mm dia including providing massonary enclosure with cover plate having welding arrangement welding pipe etc. with a ground as strip earth electrode, including connection/terminating with G.I. ma, bolt, sharcoal looke and salt as required.	Supplying and fixing copper strip bus-bars, suitable for 63 Amp. 415 volts capacity. 4. No. each of cross-sectional area (25.4mm/s.17mm), in the existing enclosure with all accessories including connections etc. as required:	63 A, 36 KA,4Pole
	-	27	N	-	-
	1740	112	4532	3680	3886
	Rupees One thousand seven hundred forty only.	Rupees One hundred twelve only.	Rupces four shousand five hundred thirty two only.	3680 Rupoes three thousand six hundred eighty only.	8880 Rupees Eight thousand eight hundred eighty only.
	Eeach	Each	P/SET	Per/mtr.	Each
242953	1740	3024	9064	3680	8880

Executive Engineer, Electrical Division, HP.PWD, Una.

Name of work :- C/O New Canteen at Govt. College Beetan, Distr. Unu (HP) (SH:- Providing E.1. therein)

r				_ 2	1.01	_	Sr. No.
Single core copper conductor cable for earthing as required.(Make :- KEI/Anchor/SSK)	(HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 2 No.4 Sq.mm. HRFRLS/PVC insulated	Wising for power plug with 4x4 Sq. may. PVC insulated hast resistant flume retaction.	(HRFR) and low snoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with I No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required.(Make :- KEI/Anchor/SSK)	Wiring for power plug with 2x4 Sq. mm. PVC Insulated heat resistant flame retardant	Group - C	Wiring for light point / fan point / exhaust fan / call beil point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required.(Finolex,KELAnchor,L&T make)	Description
111		25		30	29		Quantity
		742		453	174)		Rate
A STATE OF THE PARTY OF THE PAR	only.	Rupees seven hundred fforty two		Rupees four hundred fifty three only.	Rupees One thousand seven hundred forty one only.		In words.
		P/mar.		Pintr.	Each		Unit
		18550		13590	50489		Amount

	- Commission								
	6.02	6.01	6	5.02	5.01	ů.	4.02	4.01	
Supplying and fixing-metal-box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, piano type switch, connections, painting etc. as required.	5 pin, 5/ 6 Amps P/T socket outlet.	SP. 5/ 6 Amps one way P/T Switch	Supplying and fixing following rating P/T switch (socket in the existing switch box / cover plate including connections etc. as required. (SSK,L&T,Anchor make)	6x1.5 Sq. mm.	3x1.5 Sq. mpm.	Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed, Steel/PVC conduit as required.(Make :- KEI/Anchor/SSK)	2x10 Sq. mm.	2x).5 Sq. nxn.	Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with I No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Make :- KEI/Anchor/SSK)
	8	040		ĸ	28	-	2	700	
283	75	52		215	1 =		812	319	
Rupees Two hundred eighty three only.	Rupees Seventy five only.	Rupees fifty two only.		Rupees Two hundred fifteen only.	Rupees One hunsdred eleven only.		Rupees Eight hundred (welve only.	Rupees three hundred nineteen only.	
Each	Each	Each		P/mtr.	P/mur.	dim of the	P/mtr.	P/mtr.	
566	600	416		5375	3108	N	1624	24882	

STATE OF THE

Single pole. 6 Amps.Cat-A. Single pole. 6 Amps.Cat-A. Single pole. 16 Amps.Cat-A. Supplying and fixing of following rating.double pole,240 volts,isolator in existing MCB DB complete with connections.testing and commissioning et required:-(Make:-L&T/Legrand/Schneider) Double pole. 40 Amps.Cat-A. Supplying and fixing following rating, double pole (single phase & neutral) yolls, residual current circuit breaker (RCCH), having a sensitivity current up to miliampers in the existing MCB DB complete with connections, testing commissioning etc. as required. (Make:-L&T/Legrand/Schneider)	isolator in soning et soni	solator in the soning etc. as neutral) 240 ment up to 300 s. testing and	240 as the
le,240 volts, and commiss and commissivity of connection Schneider)	isolator in sioning et a neutral) & neutral) arrent up to ns, testing	240 as the	the 2 2 240 300
le,240 volts and commis angle phase sensitivity o	isolator in sioning et soutral)	the 240	the 2 240 300
le,240 volts, and commiss	isolator in sioning et	etc. as	in the 2
le,240 volts, and commiss	isolator in sioning et	etc. as	in the 2
le,240 volts	isolator in sioning et	etc. as	in the 2
e 240 wolk	recolator at		22 04
		5	5
	1		
32 amps. rating, 10 KA breaking breaker of following poles in the etc. as required:-(Make :-L&T/	king caps in the exi	olts, 'C' curves, miniature circuit breaker of following poles in the existing DB complete with connections etc. as required:-(Make :-L&T/Legrand/ider)	is the existing &T/Legrand/
batten/angle holder including connections	crions en	crions etc. as 2	etc. as
Supplying and fixing metal box of 180mmx (00mmx50mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 6 pin 15/16 amps socket outlet and 15/16 amps, piano type switch, connections, painting etc. as required.	ront inclus, piano	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on 2 surface/recess with suitable size phensile laminated sheet cover in the front including providing and fixing 6 pin 15/16 amps socket outlet and 15/16 amps, piano type switch, connections, painting etc. as required.	

HUR F

	Tay.						
- 1	TO I			1			
17	91	15.01		14.01	X	13.01	
Supplying and fixing exhaust fan louver shutter for 300 mm.exhaust fan on the existing wall, painting etc, as required.	Supplying and fixing Fan box of M.S.sheet with from rod hook 12 mm.in place of junction box complete as required.	Exhaust Fan, Hesvy duty, 300 mm sweep	Providing and installution of exhaust fan of following sizes in the existing opening including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required: (Usha - SPH Turbo HDEF 900 RPMISI or jts Equivalent make)	Ceiling Fan 1200 mm sweep, Category-A	Providing Installation, testing and commissioning of ceiling fan without step type fan regulator modulur, air delivery 215 m3 /min power input 30 watts speed 330 RPM, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required:-(Usha-Technixplus BEE 3 Star rated model) or its equivalent make)	Double door-12 way	Supplying and fixing of following way, single pole and neutral sheet sites of stribution board, 240 volts, on surface / secess, complete with tinned copper busbar, wire-set, neutral link, earth bar, din-bar, detachable gland plate, blanking plate, cable, identification labels interconnections, phosphatized and powder painted, including earthing etc. as required:-(Hagger, ABB, L&T make)
	10	3.		10		-	
562	45	4063		2964	- 46	2149	
Rupees Five hundred sixty only.	Rupees Forty five only.	Rupees Four thousand sixty three only.		Rupees Two thousand nine hundred sixty four only.		forly nine only.	
Each	Each	Bach		Each		Each	
1686	450	12189		29640		2149	
20				1			

13824	1 医基础管理		
20		. 19	*
Supplying and fixing LED Lamp 9 wants 6500 K E-27-,900 Lumens 240 volts AC-supply 50 HZ in the existing batten holder, pendent holder, wall bracket & bulk head-fitting etc., as required (Tisva cut. No.AL946611X/Panusonic/Philips make)	Photobiological Safety of humans. The Input voltage range shall be 150V to 270V. Fixture have Surge Protection 2kV. Driver Output voltage shall be less than SELV Limits for safe operation and maintenance Wipro Cat. No LD80-171-XXX-60-SM or Equivalent in Philips: SM251C LED20S-6500 PSU WH or Tribux: Ambiella IND D LED1000-860 ET 01 ET or LT:	Supply& Fixing of led fixture 18 W LED Surface Mounted Downlighter Round Shape with minimum system lumen efficacy of 90 lm/W with and P.F.>0.95 with THD<20%, CRI 80. The LED shall be tested with LM80-08 standard with Useful life of 50000 Hrs at L70. The LEDs used in the luminaire shall have CCT of ANSI Bin	Supply and fixing of JP40 Led fixuare 40 W with Surface Mounted 4 Feet with Polycarbonate diffuser with aluminium bousing minimum lunner output 4000 lumens with P.E.>0.95 with THD 10% CRI 80.Surge Protection 2 Kv with IP Protection of IP20. The LEDs with minimum life of 50000 burning hours. The LED shall be tested with LM80-08 standard with Useful life of 50000 Hrs at L70. The LEDs used in the luminaire shall have CCT of ANSI Bin 5700 K with CRI of minimum 80. LEDs used must be tested as per EN62471 for Photobiological Safety of humans. The Input voltage shall be 150V to 270V. Driver Output voltage shall be less than SELV Limits for safe operation and maintenance. Wipro Cat. No LL24-541-XXX-57-XX or Equivalent in Philips: BN308C LED40S-6500 L120 PSU WH or Trilux:TRL-X F OTA 4000-857 ET
2		-	5
256		2838	3004
Rupees Two hundred fifty six only.		Rupees Two thousand eight hundred thirty eight only.	Rupees Three housand four only.
Each		Each	Each
512		2838	48064
			-30

	74	23	Ħ	Sol B
Total >	Supplying and laying 6 SWG G.I. wire at 0.50 mtr. below ground level for earth electrode conductor, including soldering etc. as required.	Extra for using salt and charcoal for G.I. pipe earth electrode complete as required.	Earthing with G.1 earth pipe 4.5 mtr. long and 40mm dia, including accessories and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal or coke and sait) complete as required.	Providing and toxing LEO Street right 25 watts atturnation due cast housing with Polycarbonate LENS for uniform light distribution. AC 85-270 volts with 4MV electric surge, human 2400, available color temperature 6500 K,CRI 80,IP rating 66, up to 10KVA electric surge protection and bracket of steel conduit pipe 32 mm., complete with all accessories, connections, testing and commissioning etc, as required. (Wipro LR02-291-XXX-57-XX/Clair/Philips make)
	20	-	-	
-	46	1613	3351	4581
Designation of the last of the	Rupees farty only.	Rupees One thousand six hundred thirteen only.	Rupues three thousand three hundred fifty one only.	sixty one only.
STREET, SQUARE,	P/mtr.	P/set	P/set	9
237147	800	1613	3551	ě

Executive Engineer, Electrical Division, HP.PWD., Una.

123	110441			7 17	_	7	-			-
THE PERSON NAMED IN		1.01	-	Sr.		io sens		-		
Wiring for power-plug with 4x4 sq.mm. PVC insulated hear resistant flamerificetardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 2 NO. 4 sq.mm. HRFRLS/PV C insulated single core copper conductor cable for earthing as required. (Finolex/Anchor/KEI /Plaza make)	Wiring for power plug with 2x4 sq.mm. PVC insulated hear resistant flame- retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/ recessed steel conduit along with 1 NO, 2 sq.mm. HRFRLS/PV C insulated single core copper conductor cable for earthing as required. (Finolex/Anchor/KE1/Plaza make)	Group C	Wiring for light point/ fan point / exhaust fan/ call bell point with 1.5 sq.mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (Flexible) copper conductor cable in surface/ recessed steel conduit and earthing the light point with 1. 5sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required. (Make:- Legrand , L&T , Anchor)	Discription of Item	Tehsil Ghanari Distt. Una HP (SH: - Providing E.I. there in).	Name of work: - Construction of additional accommodation (2rooms alongwith stair) case at Govt. Sr. Sec. School Pirthipur				DRAFT SCHEDULE OF QUANTITY
	14	29		Quantity		ir) case at (
752	460	1755	31			iovt. Sr. Se				
Rupées Seven hundred fifty two only.	Rupees Four hundred sixty only:	Rupees One thousand seven hundred fifty five only.		Fig. In Words.		ec. School Pirthipur	Time Limit:- One year,	Earnest money:- Rs. 3,000/-	Estimated cost:- Rs. 1,47,263/-	Job No. 23
Per metre.	Per metre	Each		Unit					4	4
7520	6440	50895		Amount				1000	17	

and control

	411			The state of the s		A Service				
9	8		7	6.02	6.01	6.	c,	4.02	4.01	4
Supplying and erection of 6Amp to 32Amps rating 10 KA breaking capacity, 240 volts 'C' curves miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required.Category-A.(Hagger,ABB,L&T make)	Supplying and fixing bakelite batten /angle holder including connections etc. as required.	the front including providing and fixing 6 Pin 15/16 amps socket outlet and 15/16 amps piano type switch, connection, painting etc. as required. (SSK/anchor/L&T)	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recessed with suitable size phenolic laminated sheet cover in	5 pin 5/ 6 Amps socket outlet, porcelain base/ piano type.	S.P. 5/ 6 Amps one way switch, piano type,	Supplying and fixing following rating Piano-type switch /socket on the existing switch box / cover including connections etc. as required.(SSK/Anchor/L&T)	Supplying and Drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface/recessed, steel/PVC conduit as required. a) 3x1.5sq.mm. (KEI, Anchor, Finolex make)	2x10sq.mm.	2x1.5sq.mm.	Wiring for circuit/ sub main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conducotr cable in surface/recessed steel conduit along with 1 No. HRFRLS/PVC insulated single core copper conductor cableof same size for earthing as required. (KEI, Anchor, Finolex/Plaza make)
· A	6		2	. 4	4		12		38	
191	62		529	79	54		100	772	326	
Rupees One hundred ninety one only.	Rupees Sixty two only.		Rupees Five hundred twenty nine only.	Rupees Seventy nine only.	Rupees fifty four only.		Rupees One hundred only.	Rupees Seven hundred seventy two only.	Rupees Three hundred twenty six only.	
Each	Each		Each	Each	Each		Per metre	Per Meter	Per metre	
955	372		1058	316	216		1200	772	12388	N. ST.

	2.14						
1							
	15	=	13	12.01	12	=	10
	Sopplying and laying 6SWG G.1. wire at 0.50 meter below ground level for earth electrode conductor, including, soldering etc. as required, including carriage of material with in all leads and lifts.	Extra for using salt and charcoal for pipe earth electrode complete as required including carriage of material with in all leads and lifts.	Earthing with G.I. earth pipe 4.5 meter long and 40 mm dia, including accessories and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal or coke salt) complete as required.	12 way Double door (Hagger, ABB, L&T make)	Supplying and fixing of following way, single pole and neutral sheet steel MCB distribution board, 240 volts, on surface/recess, complete with tinned copper bus bur, wire-set neutral link, earth bar, din bur, detachable gland plate blanking plate, cable, indentification labels interconnections, phosphatized and powder painted, including earthing etc. as required including carriage of material with in all leads and lifts.	Supplying and fixing of following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB) having a sensitivity current up to 300 milliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required. a) 40Amp Category-A.(Hagger,ABB,L&T make)	Supplying and erection of 40/50/63Amps rating 10 KA breaking capacity, 240 volts 'C' curves miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required. Double pole Category-A-(Hagger, ABB, L&T make)
	30	-		-		1.34	
	67	2717	5873	1731	4 12	2294	383
THE PERSON NAMED IN	Rupoes sixty seven only	Rupees Two thousand seven hundred seventeen only.	Rupees five thousand eight hundred seventy three only.	Rupees One thousand seven hundred thirty one only.		Rupees Two thousand two hundred ninety four only.	Rupees three hundred eighty three only.
	Per Metre	Per Set	Per Set	Each		Each	Each
	2010	7717	5873	1731	- 6	2294	383

	20 Supplying and fixing of sub main we core aluminium conductor cable on required. (Polycab, Havells, Finolex)	Cathory (ML/)00	19 Providing and fixing rating 5kv, IP 66, in M.S.bracket 62 mm.s the existing pole includes attisfaction of Engine	and as per best satist required.(Panasonic make)	LED batten anodized steel clumps for surfa- with specifications i. efficacy > 100 Lumer	17 Supplying and fixing in place of junction t	16-01 Ceiling Fan 1200 mm sweep.	regulator, including wiring the do with 16/0.20 mm twin twisted including providing and fixing phand earthing etc. as required: Technixplus BEE 3star/ Bajaj 3
	Supplying and fixing of sub main wiring with 10 sq.mm. weather proof twin core aluminium conductor cable on the G.L.bearer wire etc, as required. (.Polycab, Havells, Finolex)	Cathors (M2/300XX/Fumps wipro make)	Providing and fixing LED streetLight 30wans. CCT 5700K, CRI>80, Surge rating 5kv, IP 66, input, voltage 140V-270v, 50Hz, A. C. Supply with M.S. bracket 62 mm. dia with die cast aluminium housing with IP diffuser on the existing pole including connections complete itrall respects and best satisfaction of Engineer-in-charge at site (Panasonic	220-240 Volts,50 HZ, Length 1175X30X36 mm.complete with connections and as per best satisfaction of Engineer-in-Charge complete as required.(Panasonic Harrow Al Code No.PBTM08368/Philips/Wipromake)	Providing and fixing LED surface/pendent mounting Tube fixture 36 warts LED batten anodized aluminium housing PC diffuser with PC end caps, spring steel clamps for surface mounting arrengement and it should be compatible with specifications i.e.Power factor >0.9.Harmonic distortion <10% & efficacy >100 Lumen per watts, CRI >80,5700 K suitable for input voltage	Supplying and fixing fan box made of M.S. sheet with iron rod Hook 12mm in place of junction box complete with Bakelite Round sheet as required.	n sweep,	regulator, including wiring the down rods of standard length (up to 30 cm) with 16-0.20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required: (CromptonWWHE ISI mark/Usha-Technixplus BEE 3star/ Bajaj 3 Star rated model)
	40		12		3	œ	50	200
	11	H	4121		1139	4	2872	
	Rupees Seventy one only,		Rupees Four thousand one hundred twenty one only.		Rupees One thousand one hundred thirty nine only.	Rupees Forty four only.	Rupees Two thousand eight hundred seventy two only.	
1	P/mtr.		Each		Each	Each	Each	
	2840		8242		14807	352	22976	1-1-1-

				-		-
147263					Total	
*					Panasonic make)	
		50			fitting etc. as required (Phillips Ace Saver HSN CODE 85395000/ Tisva/	
	1	only.			50 Hz in the existing batten holder, pendent holder, wall bracket & bulk head	
906	Each	Rupees One hundred fifty one	151	6	Supplying and fixing LED Lamp 9 watts ,825 Lumens 240 volts AC.supply	21

Executive Engineer, Electrical Division, HP.PWD., Una.

Executive Entracer, Electrical Division, HPPWD., Una.

DRAFT SCHEDULE OF QUANTITY

Job No. 09 Estimated cost:- Rs. 1,60,000/-

Earnest money:- Rs. 3,200/-

Time Limit: - Six months.

E.
Each
Each
Unit Rate

Electrical Division, HP.PWD., Una.

4	3	2	1.01	-	S. No.
Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Finolex,KEI,Anchor,L&T make)	Wiring for power plug with 4x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single sore (flexible) copper conductor cable in surface/necessed-steel conduit along with 2 No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex,KEI,Anchor,L&T make)	Wiring for power plug with 2x4 Sq. num. PVC insulated heat resistant flame returdant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with I No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make)	Group C.	Wiring for light point / fan point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required (Finolex, KEL, Anchor, L&T make)	Description
	e 26	S	54		Quantity
J.	742	ts.	1731	10	Rate In Fig.
	Rupees Seven hundred forty two only.	Rupees Four hundred fifty three only.	Rupees One thousand seven hundred thirty one only.		In words.
	P/mtr,	P/mit.	Each		Unit
1	19292	24009	93474		Amount

THE PERSON

		R				Supplying and erection of 6 umps. to 32 amps. rating, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required: (Hagger, ABB, L&T make)	=	
1	417	Each	Rupees Four hundred seventen-	417	1 6	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase, 230 volts complete as required: (SSK, Anchor make)	10	
	776	Each	Rupees Ninety seven only.	97	66	Supplying and fixing bakelife batten/angle holder including connections etc. as required: (SSK, Anchor make)	9	
H	2916	Each	Rupees Four hundred eighty six only.	486	6	Supplying and fixing metal box of 180minx100minx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 6 pin 15/16 amps socket outlet and 15/16 amps, plano type switch, connections, painting etc. as required.		A CONTRACTOR OF THE PARTY OF TH
	1415	Each	Rupces Two hundred eighty three only.	283	u	Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/speess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, piano type switch, connections, painting etc. as required.	7	
	375	Each	Rupees Seventy five only.	75	5	5 pin, 5/ 6 Amps socket outlet P/T,	6.02	
	260	Each	Rupees fifty two only.	52	s	S.P. 5/ 6 Amps one way P/T switch.	6.01	
						Supplying and fixing following rating P/T switch /socket in the existing switch box / cover including connections etc. as required.(SSK /L&T/Anchor make)	0.	
	5772	P/mtr.	Rupees One hundred eleven only.	Ξ	52	3x1.5 Sq. mm.	5.01	
					Control	Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed, Steel/PVC conduit as required (Finolex, KEI, Anchor, L&T make)	540	
	1624	P/mtr.	Rupees Eight hundred twelve	812	12	2x10 Sq. mm.	4,02	1
	9570	Pintr.	Rupees three nundred nineteen	212	300	5000	1600	1

17 Supply:	16 Extra fo	and pposition and water required		14 Supply MCB copper blankin powder	13.01 63 Am	t3 Supply volts, r 300 mi	12,01 Double	12 Supplys existing (Legran	argue twitt
Supplying and laying 6 SWG G.I. wire at 0.50 mtr. below ground level for earth- electrode conductor, including soldering etc. as required.	Extra for using salt and charcoal for G.I. pipe earth electrode complete as required.	Earthing with G.1 earth pipe 4.5 mtr. long and 40mm dia, including accessories and providing masonry enclosure with cover plate having locking arrangement and watering pipe:etc. (but without charcoal or coke and salt) complete as required.	Double door-12 way	Supplying and fixing of following way, single pole and neutral sheet steel MCB digribution board, 240 volts, on surface / recess, complete with tinned copper bus- bar, wire-set, neutral link, earth bar, din-bar, detachable gland plate, blanking plate, cable, identification labels interconnections, phospharized and powder painted, including earthing etc. as required- (Hagger, ABB, L&T make)	63 Amps. Cat-A.	Supplying and fixing following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB), having a sensitivity current up to 300 miliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required. (Hagger, ABB, L&T make)	Double pole, 63 Amps.Cat-A.	Supplying and erection of following rating, double pole 240 volts, Isolator in the existing MCB DB complete with connections etc. as required: (Legrand/Hagger/ABB/L&T make)	confidence on the Section of the Section of
8	-	插槽	2		-		-		
46	1613	3531	2290		3456		597	-	200
Rupces forty only.	Rupees One thousand six hundred thirteen only.	Rupees three thousand five hundred thirty one only.	Rupees Two thousand two hundred ninety only.		Rupees Three thousand four hundred fifty six only.		Rupces Five hundred ninety seven only.		Acres Acres as a second or a second
P/mir.	P/set	P/set	Each		Each		Each		1
1600	1613	3331	4580		3456	M	397		

22	21	20.02	20.01	26	2	10.81	-
Supplying and fixing exhaust fan louver shutter for 300 mm.exhaust fan on the existing wall painting etc, as required.	Supplying and fixing Fan box of M.S. sheet with iron rod book 12 min. in place of junction box complete as required.	Exhaust Fan, Heavy duty, 300 mm sweep	Exhaust Fan, light duty, 300 mm sweep	Providing and installation of exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required: (Usha - SPH Turbo HDEF 900 RPMISI or its Equivalent make)	Supplying and fixing Step type fan regulator (Socket type) 100 watts on the existing switch box/cover complete making connections etc,as required.(SSK/Anchor or its equivalent make)	Ceiling Fan 1200 mm sweep, Cutegory-A	Providing, installation, testing and commissioning of ceiting fan without regulator, including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required: (Usha-Technixplus BEE 3 Star rated model) /Crompton/Bajaj or its equivalent make)
	•	3	1 -		os	640	
592	45	4063	2503		487	2964	
Rupees Five hundred ninety two only.	Rupees forty five only.	Rupees Four thousand sixty three only.	Rupees Two thousand five frundred five only.		Rupees four hundred eighty seven only.	Rupees Two thousand nine hundred sixty four only.	
Each	Each	Each	Each	4	Each	Each	
2368	360	12189	2505		3896	23712	

1 1	11153 113			
26	The second second	23	2	t
Supplying and fixing LED Lamp 9 watts 6500 K E-27,900 Lumens 240 volts AC supply 50 HZ in the existing batten holder, pendent holder, wall bracket & bulk head fitting etc., as required. (Tisva car. No.AL946611X/Panasonic/Philips make)	THD-20%; CRI 80. The LED shall be tested with LM80-08 standard with Useful life of 50000 Hrs at L70. The LEDs used in the luminaire shall have CCT of ANSI Bin 6000 K with CRI of minimum 80. LEDs used must be tested as per EN62471 for Photobiological Safety of humans. The Input voltage range shall be 150V to 270V. Fixture have Surge Protection 2kV. Driver Output voltage shall be less than SELV Limits for safe operation and maintenance. Wipro Cat. No LD80-171-XXX-60-SM or Equivalent in Philips: SM251C LED20S- 6500 PSU WH or Trilux; Ambiella IND D LED1000-860 ET 01 ET or LT:	Supply& Fixing of led fixture 18 W LED Surface Mounted Downlighter Round Shape with minimum system lumen efficacy of 90 lm/W with and P.E.>0.95 with	Providing and fixing LED surface/pendent mounting Tube fixture 24 watts Jaqour make glazed LED batten Cat.No.LGLZ01X024XN high quality design aluminium extruded decorative end caps as per best satisfaction of Engineer-in- Charge complete as required.	Supply and fixing of IP40 Led fixture 40 W with Surface Mounted 4 Feet with Polycarbonate diffuser with aluminium bousing minimum lumen output 4000 lumens with P.F.>0.95 with THD<10%, CRI 80, Surge Protection 2 Kv with IP Protection of IP20. The LEDs with infinium life of 50000 burning hours. The LED shall be tested with LM80-08 standard with Useful life of 50000 Hrs at L70. The LEDs used in the luminaire shall have CCT of ANSI Bin 5700 K with CRI of minimum 80. LEDs used must be tested as per EN62471 for Photobiological Safety of normals. The Input voltage range shall be 150V to 270V. Driver Output voltage shall be less than SELV Limits for safe operation and maintenance. Wipro Cat. No LL24-541-XXX-57-XX or Equivalent in Philips: BN308C LED405-6500 L120 PSU WH or Trilux:TRL-X F OTA 4000-857 ET
ec		9	6.	=======================================
256		2338	876	3004
Rupees Two hundred fitty six only.		Rupees Two thousand three hundred thirty eight only.	Rupees Eight hundred seventy six only.	Rupees three thousand four only.
Each		Each	Each	Each
2048		21042	5256	36048

	29	. 28	27
,	Wiring for sub main w conductor cable on G.1	Supplying and fixing of The LEDs used in the 80 with LM80 tested L No LS06-005-120-40-	Providing and fixing L 85-270 volts available 10KVA electric surge connections testing and No.LR 02 -671-XXX-
Total	Wiring for sub main wiring with 16 sq.mm, weather proof twin core aluminium conductor cable on G.I.bearer wire etc.as required.	Supplying and fixing of IP20 LED Strip light in 25 W in Strat Speed with CRI>80. The LEDs used in the luminaire shall have CCT of 4000K with CRI of minimum 80 with LM80 tested LEds driver for strip light should be included Wipro Cat. No LS06-005-120-40-50+LG40-024 or Equivalent in Philips / OSRAM.	Providing and fixing LED Street light 60 watts the cast aluminium housing.AC 85-270 volts available color temperature 5700 K,CRI 80,IP rating 66, up to 10KVA electric surge protection complete with all Bracket, accessories, connections,testing and commissioning etc.as required. (Wipro Skyline Code No.LR 02 -671-XXX-57-G2/Clair/Philips make)
	4	6	0
1	67	2692	10583
	Rupees sixty seven only.	Rupees Two thousand six hundred ninety two only.	eighty three only.
1	P/mtr.	Each	Each
370586	3015	16152	63498

3 Wiring for power plug with 2x4 Sq retardant (HRFR) and low smoke cable in surface/recessed steel HRFRLS/PVC insulated single cor required.(Make:-KEI,Anchor,SSK.)	2.01 Group C	2 Wiring for twin control light poresistant flame retardant (HRFI conductor cable in surface/recemodular switch, modular plates with 1.5 Sq.mm. HRFRLS/PV(as required (Make:-Legrand (Make	1.01 Group C	sq.mm Wiring for light point/ fan point/ exhaust fa sq.mm Wiring for light point/ fan point/ exl 1.5 sq.mm FRLS PVC insulated copper corsurface / recessed steel conduit, with modu GI box and earthing the point with 1.5 sq.m conductor single core cable etc as required.	No.	NAME OF WORK :- C/O Way side A				DRAFT SC
Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with I No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required.(Make:-KEI,Anchor,SSK.)	The state of the s	Wiring for twin control light point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit with 2-way, 5/6 amps. modular switch, modular plates, suitable G.I. box and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required.(Make:-Legrand (Myrius),L&T(Oris/Entice), Anchor(Roma plus)		Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.	DESCRIPTION	NAME OF WORK :- C/O Way side Amenities at Jogi Panga District Una (H.P.)(S.H:-Providing E.L Therein).				DRAFT SCHEDULE OF QUANTITY
35 Meter	1 Points		35 Points		Quantity	t:-Providing I			1	
453	1838		1720		Rate In fig.	E.L. There				
Rupees Four hundred fifty three only.	Rupees One thousand eight hundred thirty eight only.		Rupees One thousand seven hundred twenty only.		In words.	ein).	Time Limit: One year.	Earnest money:- Rs. 5,700/-	Estimated cost:- Rs. 2,82,796/-	Job No. 11
PMtr	P/Point		P/Point	7	Unit					
15855	1838		60200		Amount					7

	_	Page 2	2				
		Wiring for power plug with 4x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 2 No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required.(Make:-KEI,Anchor,SSK.)	35 Meter	742	Rupees Seven hundred forty two only.	P/Mtr	25970
	· Sh	Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Make:-KEI,Anchor,SSK.)					
	5.01	2x1.5 Sq. mm.	75 Meire	319	Rupees three hundred nineteen only.	P/Mir	23925
	5.02	2x10 Sq. mm.	12 Metre	812	Rupees Eight hundred tweleve only.	P/Mtr	9744
	•	Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed, Steel/PVC conduit as required.(Make:-KEl,Anchor,SSK)					
	6.01	3x1.5 Sq. mm.	52 Meire	Ε	Rupees One hundred eleven only.	P/Mtr	5772
the state of the s	7	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase,230 volts complete as required:-Makes:-L&T/Anchor/Philips.	Nos	742	Rupees Seven hundred forty two only.	Each	742
	or .	Supplying and fixing G.I. Modular box of (140mmx78mmx50mm) size with modular plate and cover in recess including providing and fixing 5 pin 5/6 amps modular socket outlet and 5/6 amps, modular switch, connections etc. as required(Make:-Legrand (Myrius), L&T(Oris/Entice), Anchor(Roma plus)	7 Nos	643	Rupees Six hundred forty three only.	Each	4501
1	٠	Supplying and fixing G.I. Modular box of (140mmx78mmx50mm) size with modular plate and cover in recess including providing and fixing 6 pin 15/16 amps modular socket outlet and 15/16 amps, modular switch, connections etc. as required. (Make:-Legrand (Myrius),L&T(Oris/Entice),Anchor(Roma plus)	7 Nos	999	Rupces Nine hundred ninety nine only.	Each	6993

15190	Each	Rupees three thousand thirty eight only.	3038	Nos	5	Ceiling Fan 1200 mm sweep (Make: Usha, Model: Technix Plus)/Bajaj(Model: Sabae Tezz Kassels)/Crompton(Model: WWHE).	14.01
					1.	Providing Installation testing and commissionning of ceiling fan with socket size modular steo type electronicfanregulator including wiring the down rods of standardlengh (Up to20 cm) with 16/0.20 minitwin twisted flexible,cotton braided copper cable,includingproviding and fixing phenolic laminated sheet cover on the fan box and earling etc. as required.	-
2876	Each	Rupees Two thousand eight hundred seventy six only.	2876	Nos	Barrell	13.01 Dooble door 16 way Makes. L&T/Legrand/Schnelder/Stavelt.	3,01
						gland plate, blanking plate, cable, identification labels interconnections, phosphatized and powder painted, including earthing etc. as required:-	
			I P	10		Supplying and fixing of following way, single pole and neutral sheet steel MCB distribution board, 240 volts, on surface / recess, complete with	13
3489	Each	Rupees three thousand four hundred eighty nine only	3489	Nos	_	63 Amps. Cat-A.Makes:- L&T/Legrand/Schneider/Havell	12.01
						Supplying and fixing following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB), having a sensitivity current up to 300 miliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required.	2
566	Each	Rupees Five hundred sixty six only.	566	Nos	-	63 Amps. Car-A.Makes:- L&T/Legrand/Schneider/Havell	11.01
-				21	-	Supplying and fixing following rating, double pole, 240 volts, isolator in the existing MCB DB complete with connections, testing and commissioning etc. as required.	=
2530	Each	Rupees Two hundred thirty only.	230	Nos	=	Single pole. Cat-AMakes:- L&T/Legrand/Schneider.	10.01
	3				-46	capacity, 240 volts, 'C curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-	ā

	3	distortion ≤ 10% and efficacy ≥ 100 lumens per watt, CRI > 80, suitable for input voltage AC 220-240V, 50/60 Hz, including one no. tube rod 20 Watt complete with all accessories, connections, testing and commissioning etc, as required. Including five years warranty as required.	1
		Providing and fixing decorative extruded tube fixture having high quality design suitable for LED tube up to 20 Watt (2000 lumen) 6500K and it should be compatible with specifications i.e. power factor \geq 0.9, harmonic	18
Rupets Two thousand one hundred one only.	7 Nos. 2101	Cat Nq:-Wipro(LW07-141-XXX-57-G)-10Warts)/Panasonic/Bajaj or Lucial Equivalent.	17.01
		input voltage AC 220-240V,50/60 Hz complete with all accessories, connections, testing and commissioning etc. including five years warranty as required.	
	THE STATE OF THE S	:Supplying and fixing Bulk Head LED 10 Watt (1000 lumen), 5700K and it should be compatible with specifications i.e. power factor \geq 0.9, harmonic distortion \leq 10% and efficacy \geq 100 lumens per watt.CRI > 80 suitable for	17
Rupees Ten thousand seven hundred seventy nine only.	4 Nos. 10779	Cat No :- WIPRO(LF19-711-060-57-XX-60Warts)/Panasonic/Bajaj or equivalent.	16.01
		Supplying and fixing LED Flood Light 60 Watt (6000 lumen), 5700K and it should be compatible with specifications i.e. power factor ≥ 0.9, harmonic distortion ≤ 10% and efficacy ≥ 100 lumens per watt, CRI > 80, suitable for input voltage AC 220-240V, 50/60 Hz complete with all accessories, connections, with angle iron frame testing and commissioning etc.Including five years warranty as required.	16
Rupees Two thousand one hundred seventy seven only.	4 Nos 2177	Exhaust Fan, Light duty, (Domestic) 300 mm sweep Makes:- Usha/Crompton/Anchor	15.01
		Providing and institution of extraust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning including shutter etc. as required:	5

になった。

e 70 4199 659 90
e 50 Rupees Fifty only. Rupees Fifty only. Rupees Seventy only. Rupees Seventy only. Rupees Seventy only. Rupees Six hundred fifty nine only. Executive Engineer Executive Engineer
Rupees Four thousand one hundred ninety nine only. Rupees One thousand sixty one anly. Rupees Fifty only. Rupees Seventy only. Rupees Ninety only. Rupees six hundred fifty nine only. Executive Engineer Electrical Division HP PWD Una
P P P
Per Set Por Set P/Mir P/Mir Each Each

DRAFT SCJHEDULE OF QUANTITY

Job No. 12

building at Jankour, Distt. Una. (HP)(SH:-Providing E.I fan / call bell point with 1.5 Sq. dant (HR.FR) and low smoke single surface/recessed steel conduit and RFRLS/PVC insulated single core (KEI, Anchor, L&T make) C insulated heat resistant flame (flexible) copper conductor cable No.1.5 Sq. mm. HR.FRLS/PVC for earthing as (flexible) copper conductor cable No.4 Sq. mm. HR.FRLS/PVC for earthing as					Estmated cost:- Rs. 1,95,624/-			
No. Description Description Description Ountity Rate In words. Unit As In Fig. Wiring for light point / fan point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HBFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earling the light point with 1.5 Sq. mm. HFRLS/PVC insulated single core copper conductor cable as required. (Finolex,KELAnchor, L&T maker) From PVC insulated heat resistant flame retardant (HBFR) and low smoke single core copper conductor cable as required. (Finolex,KELAnchor, L&T maker) From PVC insulated heat resistant flame retardant (HBFR) and low surface/recessed steel conduit and earling as required. (Finolex,KELAnchor, L&T maker) From PVC insulated single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.; 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HBFR) and low surface cable for earthing as required. (Finolex,KELAnchor, L&T maker) Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HBFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.; 1.5 Sq. mm. HRFRLS/PVC insulated heat resistant flame only. Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame in surface/recessed steel conduit along with 1 No.; 1.5 Sq. mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required. (Finolex, KELAnchor, L&T maker) Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame only. But 1.5 Sq. mm. PVC insulated heat resistant flame only. Skiny sweat only. Ski					Time Lomit:- One year.			95
No. Description Quantity Rate In words. Unit Ax Wiring for light point / fan point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flane evandant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLSPVC insulated single core copper conductor cable as required (Finolex,KEI,Anchor,L&T maker) Proper Conductor cable as required (Finolex,KEI,Anchor,L&T maker) 2 Group C. 101 Group A. 102 Group C. 103 Rupees One thousand three bundred single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq.mm. HRFRLSPVC insulated single core copper conductor cable for earthing as required (Finolex,KEI,Anchor,L&T maker) 3 Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.4 Sq.mm. HRFRLSPVC insulated single core copper conductor cable for earthing as required (Finolex,KEI,Anchor,L&T maker) 3 Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and flame proper conductor cable for earthing as required (Finolex,KEI,Anchor,L&T maker) 3 Wiring for light point vital 2x4 Sq. mm. PVC insulated heat resistant flame only. 10 319 Rupees flow thundred fifty three prints. 10 319 Rupees flow thundred fifty three prints. 10 319 Rupees flow thundred fifty three prints.	MAN	E OF WORK :- Construction of Sub Centre building at Jankour, Distt. Una. (HF	*)(SH :-Pr		Ltherein)			
Wiring for hight point / fan point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq. mm. HRFRLSPVC insulated single core copper conductor cable as required (Finolex,KE1,Anchor,L&T make) Group C. Group C. Group C. Group C. Group C. Group C. Wiring for light plug with 2x1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low spoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq. mm. HRFRLSPVC maulated single core copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq. mm. HRFRLSPVC required (Finolex,KE1,Anchor,L&T make) Wiring for power plug with 2x4.Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.4.Sq. mm. HRFRLSPVC insulated single core copper conductor cable for earthing as required (Finolex,KE1,Anchor,L&T make) Wiring for light plug with 2x4.Sq. mm. PVC insulated heat resistant flame 10 319 Rupces flore hundred fifty three required (Finolex,KE1,Anchor,L&T make) Wiring for power plug with 2x4.Sq. mm. PVC insulated heat resistant flame 10 319 Rupces flore hundred fifty three. Pintt. Fault Sixty seven only. 12 Sq. Rupces flore hundred fifty three. 13 Rupces Four hundred fifty three. 14 ASS Rupces Four hundred fifty three. 15 Pintt.	10000	Description		Rate In Fig.		Unit	Amount	
Group C. Group	-	Wiring for light point / fan point / exhaust fan / call bell point with 1.5 Sq. mm. PVC insulated heat resistant flame returdant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit and earthing the light point with 1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable as required.(Finolex,KEI,Anchor,L&T make)				-		
Group C. Group C. Wiring for light plug with 2x1.5 Sq. mm. PVC insulated heat resistant flame retardant (PHRFR) and low sgoke single core (flexible) copper conductor cable in surface/recessed steel conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make) Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make) Pintr. 20 1867 ruppees One thouseand five hundred inverse on the conductor cable in surface/recessed steel conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make)	10.1		16	1395	Rupees One thousand three hundred ninety five only.	Each	22320	
Wiring for light plug with 2x1.5 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low spoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex,KELAnchor,L&T make) Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame in surface/recessed steel conduit along with 1 No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex,KELAnchor,L&T make)	1.02	Group C.	20	1567	rupoes One thousand five hundred	Bach	31340	
Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex, KEI, Anchor, L&T make)	12	Wiring for light plug with 2x1.5 Sq. mm. PVC insulated heat resistant flame netardant (HRFR) and low sgnoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.1.5 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required (Finolex, KELAnchor, L&T make)	10		Rupees three hundred nineteen only.	P/mtr.	3190	E 121 111
	4	Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 1 No.4 Sq.mm. HRFRL S/PVC insulated single core copper conductor cable for earthing as required (Finolex, KEL, Anchor, L&T make)	. 4	453	es Four hundred fifty thre	P/max.	19932	- 14

-	7.02	7,01)	6.01		0	5.02	5.01	4	4
Supplying and fixing metal box of 180mmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 5 pin 5/6 amps socket outlet and 5/6 amps, piano type switch, connections, painting etc. as required.	5 pin 5/ 6 Amps socket outlet, porcelain base/ piano type.	S.P. 5/ 6 Amps one way switch, pinno type:	Supplying and fixing following rating Piano-type switch /socket on the existing switch box / cover including connections etc. as required.	3x1.5 Sq. mm.		Supplying and drawing following size of PVC insulated, heat resistant, flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in existing surface / recessed, Steel/PVC conduit as required. (Finolex, KEL, Anchor, L&T make)	2x10 Sq. mm.	2x1,5 Sq. mm.	Wiring for circuit/sub-main with following size PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with I No.HRFRLS/PVC insulated single core copper conductor cable of same size for earthing as required.(Finolex,KEI,Anchor,L&T make)	Wiring for power plug with 4x4 Sq. min. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed steel conduit along with 2 No.4 Sq.mm. HRFRLS/PVC insulated single core copper conductor cable for earthing as required.(Finolex,KEI,Anchor,L&T make)
6.	4	4		25			3	33		2
283	75	22		Ш	Total I		812	319		142
Rupees Two hundred eighty three only.	Rupees Seventy five only,	Rupees fifty two only.		Rupees One hundred eleven only.			Rupees Eight hundred (welve only,	Rupees three hundred nineteen only.		only.
Each	Each	Each		P/mtr.	Witness		P/mstr.	P/mtr.		Pinte.
8691	300	208		2775	The state of the s		2436	10527		17808

	Rupees three thousand four hundred fifty six only.	3456	. 2	63 Amps. Cat-A.	14.01
			100	Supplying and fixing following rating, double pole (single phase & neutral) 240 volts, residual current circuit breaker (RCCB), having a sensitivity current up to 300 miliampers in the existing MCB DB complete with connections, testing and commissioning etc. as required.	1
cty seven	Rupees five hundred ninety seven only.	597	10	Double pole. 63 Amps, Cut-A:	13.01
				Supplying and erection of following rating, double pole 240 volts, Isolator in the existing MCB DB complete with connections etc. as required:- (Legrand/Hagger/ABB/L&T make)	=
y only.	Rupees Two hundred thirty only	230	٥	16Amps.Single pole, Cat-A.	12.02
y only.	Rupees Two hundred thirty only.	230	6	6Amps.Single pole. Cat-A.	12.01
				Supplying und crection of 6 amps. to 32 amps. rating, 10 KA breaking capacity, 240 volts, 'C' curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-	12
iteen	Rupees Four hundred seventeen only.	417	2	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase,230 volts complete as required:- (SSK,Anchor make)	=
	Rupees Ninety seven only.	97	06	Supplying and fixing bakelite batten/angle holder including connections etc. as required:- (SSK,Anchor make)	5
SZ	Rupees Four hundred eight siz only.	486	0	Supplying and fixing metal box of 180nnmx100mmx60mm deep (nominal size) on surface/recess with suitable size phenolic laminated sheet cover in the front including providing and fixing 6 pin 15/16 amps socket outlet and 15/16 amps, pinno type switch, connections, painting etc. as required.	٠

2922	Each	Rupees four hundred eighty seven only:	487	0	Supplying and fixing Step type fan regulator (Socket type) 100 watts on the existing switch box/cover complete making connections etc., as required.(SSK/Anebor or its equivalent make)	21	,
270	Each	Rupees forty five only.	45	. 6	Supplying and fixing Fan box of M.S.sheet with iron rod hook 12 mm.in place of junction box complete as required.	20	
MORE	Early	Rupers Two thousand nine hundred sixty four only.	2964	6	Ceiling Fan 1200 mm sweep, Category-A	10.01	0.5
					Providing, Installation, testing and commissioning of ceiling fan without step type fan regulator modular, power input 30 wasts speed 330 RPM.including wiring the down rods of standard length (up to 30 cm) with 16/0/20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required: (Usha-Technixplus) or its equivalent make)	5	
1400	P/mt.	Rupees forty only.	46	35	Supplying and laying 6 SWG G.I. wire at 0.50 mtr. below ground level for earth electrode conductor, including soldering etc. as required.	55	
1613	P/şet	Rupees One thousand six hundred thirteen only.	1613	-	Extra for using salt and charcoal for pipe earth electrode complete as required.	17	
3531	Piset	Rupees three thousand five hundred thirty one only.	3531	-	Earthing with G.I. earth pipe 4.5 mtr. long and 40mm dia, including accessories and providing masomy enclosure with cover plate having locking arrangement and watering pipe etc. (but without charcoal or coke and salt) complete as required.	16	4
4580	Each	Rupees Two thousand two hundred ninety only.	2290	2	Double door-12 way	10.5	
					MCB distribution board, 240 volts, on surface / recess, complete with tinned copper bus- bar, wire-set, neutral link, earth bar, din-bar, detachable gland place, blanking plate, cable, identification labels interconnections, phosphatized and powder painted, including earthing etc. as required:-	5	

Each 2048	Rupees Two hundred fifty six only.	256		Supplying and fixing LED Lamp 9 watts 6500 K E-27,900 Lumens 240 volts. AC. supply 50 HZ in the existing batten holder pendent holder wall bracket &
	hundred eighty three only.			voltage 220-240 Volts,50 HZ, Length 232x Width 105x Height 50 mm size complete with connections etc.as required (Panasonic Ellipto Code No.PBHM01107/Philips/ Decon or its equivalent make)
Each 1383	Rupees One thousand three	1383	-	Supplying: and fixing of Bulk head fitting LED 10 watts and suitable for input
Each 2368	Rupees Five hundred ninety two only.	592	4	Supplying and fixing exhaust fan louver shutter for 300 mm.exhaust fan on the existing wall,painting etc, as required. (National or its equivalent make)
Each 10020	Rupees Two thousand five hundred five only.	2505	4	Exhuust Fin, Light duty, 300 mm sweep
				Providing and installation of exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good the damages, connections, testing and commissioning etc. as required: (Usha - SPH Turbo HDEF 900 RPMISI or its Equivalent make)
Each 13083	Rupees Four thousand three hundred sixty onle only.	4361	ш	Providing and fixing LED Street light 25 watts aluminium die cast housing with Polycarbonute LENS for uniform light distribution and bracket of steel conduit pipe 32 mm., complete with all accessories, connections, testing and commissioning etc., as required. (Wipro LR02-291-XXX-57-XXX/Clair/Philips make)
Each 5256	Rupees Eight hundred seventy six only.	876	٥	Providing and fixing LED surface/pendent mounting Tube fixture 24 watts Jaqour make glazed LED butten Cat.No.LGLZ01X024XN high quality design aluminium extraded decorative end caps as per best satisfaction of Engineer-in- Charge complete as required.

					•	
195624					Total:-	
					Trilux:TRL-X F OTA 2000-857 ET or LT	
					65NE3 or Equivalent in Philips: BN 021 LED10S- 6500 PSU GR S1 or	
					SELV Limits for safe operation and maintenance. Wipro Cat. Nol.L20-111-XX-	_
					voltage range shall be 150V to 270V. Driver Output voltage shall be less than	
		only.			diffuser and with extruded aluminum housing/polycarbonate housing. The Input	
1440	Each	Rupees Seven hundred Twenty	720	2	8 Supply and fixing of 2ft Led Batten 10 W surface mounted with polycurbonate	28

			-	S. No.	Name o				
TOTAL	Genral/Mitsubsr or equivalent as approved by the Engineer Charge.	approximately. 3mrs long 2 nos copper pipe with insulator for inlet and outlet approximately 3 mtrs long and M.S power coated frame /stand for erection of out door unit of split type A., C including carrigae of material with in all leads and lift. Make -Daikin (model:FTHT50), O	Supplying and fixing 1.5 ton invertor split type air conditioner Hot and Cold with vlotage stablizer 150 V TO 290 V, advanced filter ,E saver mode , quit mode, dual display ,auto clean ,anti bacteria filter jet Cool on/off timer sleep mode compressor cord less remote complete in all respect as per comprising to ISI with latest amendment suitable to operate on 230 volt /240 volt + 10 % AC supply capable to perform the function of cooling dehumidification air circulation ventilation and fitting in size of nominal cooling capacity and drain pipe 20 mm dia	Description	Name of Work:- A/R M/O in various Govt. Non Residential Building under ESD Bilaspur H.P (SH:-Providing & Fixing 2 nos Air Conditioner 1.5 ton capacity in S.E. 10th Circle Office at Bilaspur in Distt. Bilaspur H.P.				DRAFT SCHEDULE OF QUANTITY
1.50			2	Quantity	ESD Bilasp				
			75991	Rate In Fig.	or H.P (S				
2017年三世紀を車が			Rupees Seventy five thousand nine hundred ninety one only.	Quantity Rate In In words.	H:-Providing & Fixing 2 no	Time Limit: Six months.	Earnest money:- Rs. 3,100/-	8	Job No. 13
A Company			Each	Unit	as Air Cond			2/-	
151982			151982	Amount	itioner 1.5				

	4.02	4.01	- 6	3,02	3.01		u	2	-	S. No.	Name of					
Supplying and fixing G.I. Modular bax of (14thmrsx78mmsx50mm) size with modular plate and cover in recess including providing and fixing 6 pin 15/16 amps modular socket outlet and 15/16 amps, modular switch, connections etc. as required.(L&T/Anchor/SSK make)	5 pin, 5/ 6 Amps Modular socket outlet.	S.P. 5/ 6 Arrigineeric way Modular switch.	Supplying and fixing following rating Modular switch /socket in the existing switch box / cover plate including connections etc. as required L&T/Ancher/SSK make)	6x1.5 Sq. mm.	3x1.5 Sq. mm.	Anchor,L&T make).	Supplying and drawing following size of PVC insulated, heat resistant, flame returdant (HRFR) and low smoke single core (flexible) copper conductor cable in recessed. Specially conduit us required	Wiring for power plug with 4x4 Sq. mm. PVC insulated heat resistant flame retardant (HRFR) and low smoke single core (flexible) copper conductor cable in surface/recessed PVC conduit along with 2 No.4 Sq.mm. HRFRLS/PVC insulated single coregopyer conductor cable for earthing as required (Finoles, KEL, Anchor, L&T make)	Wiring for power plug with 2x4 Sq. mm. PVC insulated heat resistant flame returning (HRFR) and low analte single core (flexible) copper conductor cable in surface/recessed PVC conduit along with I No.4 Sq.mm. HRFRLS:PVC insulated single core capper conductor cable for carthing as required. (Finolex,KEL,Anchor,L&T make)	Description	Name of work :-Replacement of Switch Modular in place of P/T, Celling fans, Tube flatures, Geysers etc.in Distr.& Sesion Judge residence Una, Distr. Una (HP)				DRAFT SCHEDULE OF QUANTITY	
24	43	135		20 -	8			ū	×	Quantity	rei, Geyser					
1051	203	149	1	253	137	41		404	278	Rate In fig.	s etc.in f		100			
Rupees One thousand fifty one only.	Rupees Twohundred three only.	Rupees One hundred forty nine only.		Rupees Two hundred fifty three only.	Rupees One hundred thirty seven only.		大学 の一次 から	Rupees Four hundred four only.	Rupees Two hundred seventy eight only.	-	listt.& Sesion Judge residence Una, Dis	Time Limit: Six months.	Earnest money:- Rs. 4,400/-	Estimated cost:- Rs. 2,15,868/-	Job No. 14	
Each	Each	Each	ý	-Pintr.	P/mtr.			P/mtr.	P/mir.	Unit	tt.Una (HP)				100	
25224	8729	20115	SEC	5060	7946		1	6060	9730	Amount						

-	Rupees Twothousand nine hundred sixty four only.	2964	3	Ceiling Fan 1200 nun sweep, Category-A	11.01	-
de la			1	Providing, Installation, testing and commissioning of celling fan without step type fan regulator modular, air delivery 215 m3 /min power input 30 watts speed 330 RPM, including wiring the down rods of standard length (up to 30 cm) with 16/0.20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required:-(Usha-Subse Tex 3 Star rated model) or its equivalent make)	1	O Secure
100	Rispees Four thousand one hundred ninety three only.	4193	9	Celling Fan 1200 mm sweep, Category-A	10.01	2000
				Providing, Installation, testing and commissioning of ceiling fan without step type fan regulator modular, air delivery 215 m3 /min power input 30 watts speed 330. RPM,including wiring the down rods of standard length (up to 30 cm) with 16/0.20 mm twin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic luminated sheet cover on the fan box and eurthing etc. as required:-(Havells make Astura model)or its equivalent make)	10	
Each	Rupees Eight hundred sixty six only.	866	Z	Supplying and fixing stepped type Modular fan regulator on the existing modular box including making connections etc. as required.(SSK,L&T,Anchor make)	9	
Each	Rupees Eighteen thousand five hundred forty nine only.	8549	-	Providing and installation of stationary storage type Electric water heater (Geyser) vertical 25 ltrs capacity by means of Expansion-bolts with nuts and washers, including embedding of expansion-bolts in the wall, providing and fixing of Non-return valve, Dead weight safety valve, 2 No C.P. connection rods 18* long, making good the damages, electrical connections, safety valve connections, testing and commissioning etc. as required:- (Jaquar Erica Digital EDR-WHT-V025/Recold make)		
Each	Rupees Four hundred seventen only.	417	-	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase,230 voits complete as required-(SSK_Anchor make)	7	
Each	Rupees Eight hundred thirty seven	837	16	12 modules	6,04	
Each	Rupees four hundred ninety three	493	13	6 modules	6,03	
Each	Rupees Three hundred sixty one only.	361	22	4 modules	6.02	
Each	Rupees Two hundred forty six only.	246	16	2 modules	6.01	
				Supplying & fixing of G.L modular boxes of following sizes along with modular base and cover plate for modular switches in recess as required: (L&T/Anchor/SSK make)	6	/

215868	-	The second of		13	Total t-	
3720	Pinu.	Rupees sixty two only.	23	60	Wiring for sub-main wiring with following sizes of weather proof twin core aluminium conductor cable on G.I.bearer wire etc.an required.	17
P					required (Fanasonic Empio Code No. Fibrilyio) 10 //Fibrilys/ Juquor/1 sys make)	2375
2766	Each	Rupees One thousand three hundred eighty three conly.	1383	2	Supplying and fixing of Bulk head fitting LED 10 watts and it should be compatible with specifications (i.e.Power factor >0.9.Hurmonic distortion <10% & efficacy >100 Lumen per watts, CRI >80 ,6500 K suitable for input voltage 220-240 Volts, 50 HZ, Length 232x Width 105x Height 50 mm size: complete with connections etc., as	16
1280	Each	Rupees Two hundred fifty six only.	256	K .	Supplying and fixing LED Lamp 9 watts 6500 K E-27, 900 Lumens 240 volts AC-supply 50 HZ in the existing batten holder-pendent holder-wall bracket & bulk head fitting etc, as required.(Tisva.cat. No.AL946611X/Panasonic/Philips make)	15
7008	Each	Rupees Eight hundred seventy six only.	876	*	Providing and fixing LED surface/pendent mounting Tube fixture 24 wants Jaqour make glazed LED batten Cat.No.LGLZ01X024XN high quality design aluminium extruded decurative end caps as per best satisfaction of Engineer-in-Charge complete as required.	x.
1440	Each	Rupees Seven hundred twenty only.	720	13	Supply and fixing of 2ft Led Batten 10 W surface mounted with polycarbonate diffuser and with extruded abanimum housing/polycarbonate housing minimum humen output 1000 humens P.F.>0.95 with THD<20%, CRI 80,Surge Protection 2 Kv with IP Protection of IP20. The LEDs with minimum life of 50000 The LEDs used in the luminaire shall have CCT of ANSI Bin 65000 K with CRI of minimum 80. LEDs used must be tested as per EN62471 for Photobiological Safety of humans. The Input voltage range shall be 150V to 270V. Driver Output voltage shall be less than SELV Limits for safe operation and maintenance, Wipro Cal. Nol.1.20-111-XX-65NE3 or Equivalent in Philips: BN 021 LED10S-6500 PSU GR S1 or Trilux:TRL-X F OTA 2000-857 ETor LT	5
8684	Each	Rupees Two thousand one hundred seventy one only.	2171		Supplying and fixing Exhaust fan (Plasik) with louver shutter 300 mm. 1000 RPM. 1125 Air Delivery (CMM) on the existing opening in/e making proper hole and providing 6 mm.ply board cover complete with connections etc. as required.(Bajaj Make)	12

6992	Each	Rupees One thousand seven hundred forty eight only.	1748	4	MCB DB 4 WAY	3.01	3
					MCB distribution board, 240 volts, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, inter- connections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator,Make:-L&T,ABB,Heggar.	3	
6372	Each	Rupees One thousand five hundred ninety three only.	1593	4	15 amp MCB TPN	2.01	6
			and Administration		volts, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.		1911
4780	Each	Rupees One thousand one hundred ninety five only.	1195	4	15 amp MCB TP	1.01	
1				200.0	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.	-	
Amount	Unit	In In words.	Rate In	Quanity	o. Description of Items	S. No.	
		mirpur Distt Hamirpur (H.P)	KGMC Ha	at Dr. R	Name of work - Providing power supply for Tower AC in Lecture Hall at Dr. RKGMC Hamirpur Distt Hamirpur (H.P)	Name of v	
		Time Limit:- Six months.					
		Earnest money:- Rs. 2,600/-					
	1	Estimated cost:- Rs.1,26,298/-					
		Job No. 15			DRAFT SCHEDULE OF QUANTITY		

of 125 amp insulated phase bus bur /neutral bar with shrould's /earth bar slicking saddles cement spill protector /colour coded interconnected wire set /eable ties/blanking plate and circuit indentification labels. SP/TP MCB as out going Powder painted including earthing et as required.Make:-L&T (code- DBVTLO006DD)/ Legrand.Hagger , or its equivalent as approved by Engineerin charge. Providing, laying and fixing of PVC round sheathed 6 core 4sqmm copper conductor flexible cable for voltage grade up to 1100 volt, on surface/recess PVC conduit as required complete in all respect. Make:-Finolex/Havell/Polycab/KEI or it equivalent. Providing, laying and fixing of PVC round sheathed 5 core 2.5sqmm copper conductor flexible cable for voltage grade up to 1100 volt, on surface/recess PVC conduit as required complete in all respect. Make:-Finolex/Havell/Polycab/KEI or it equivalent. Providing, laying and fixing of fellowing sizes of Heavy class only. 1-21 Supplying and fixing of following sizes of Heavy class only. PVC conduit wall thickness minimum 2.0 mmt along with accessories insurface freess including painting in case of surface conduit, or cutting the walland making good the same in case of recessed conduit as required. MAKE:- BEC.DIPLAST.AKG Rupees One hundred thirty only.	4			On .	6	The same of the sa	7	
334	Supplying and fixing of VERTICAL TPN DB 6 way, sheet steel MCB distribution board 415 Volt on surface /recess with provision to mount MCCB as incomer with provision	of 125 amp insulated phase bus bar /neutral bar with shroud/s /earth bar sticking saddles cement spill protector /colour coded interconnected wire set /cable ties/blanking plate and circuit indentification labels .SP/TP MCB as out going ,Powder painted including earthing etc as	required.Make:-L&T (code- DBVTL0006DD)/ Legrand,Hagger, or its equivalent as approved by Engineer- in charge.	Providing, laying and fixing of PVC round sheathed 6 core 4sqmm copper conductor flexible cable for voltage grade up to 1100 volt, on surface/recess PVC conduit as required complete in all respect. Make :-Finolex/Havell/Polycab/KEI or it equivalent.	Providing, laying and fixing of PVC round sheathed 5 core 2.5sqmm copper conductor flexible cable for voltage grade up to 1100 volt, on surface/recess PVC conduit as required	or it equivalent.	1.21 Supplying and fixing of following sizes of Heavy class PyC conduit wall thickness minimum 2.0 mmt along with accessories insurface/recess including painting in case of surface conduit, or cutting the walland making good the	same in case of recessed conduit as required. MAKE:- BEC,DIPLAST,AKG
1 特別 銀 海 ()	===	-		90	20		75	
Rupees four hundred nincty only. Rupees three hundred thirty only. Rupees One hundred thirty only.	13580			491	334		139	71
uine four	Rupees thirteen thousand five hundred eighty only.			Rupees four hundred ninety one only.	Rupees three hundred thirty four only.		Rupees One hundred ijhirty nine only.	
MTR	Each			MTR			Meter	
44190	13580			44190	6680		10425	

	11.01		10.01	10		7.
Total	1 4x16 sq mm(28 mm)	Supplying and making end termination with brass compression glnd and aluminium lugs forfollowing size of PVC sheathed /XLPE aluminium conductio cable of 1.1kv grade as required	Armoured cable 16 sq. mm (four core)	Providing & Laying of one number aluminium conductor, PVC insulated and PVC sheathed armoured/ XLPE power cable, P1 KV grade of following sizes on wall surface as required. Make:-KEI,POLYCAB, PLAZA or its equivalent as approved by Er-in-charge	Supplying and fixing of 4 pole MCCB 63Amp. Ics = 100% ICU, 25KA & @ 415 volts, 50 Hz. with thermal magnet in release complete with connection, testing and commissioning etc as required. Make:- L&T, Legrand. Hagger, or its equivalent as approved by Engineer-in-charge.	Supplying and fixing of DLP U PVC of size 105x50 mm adaptable trunking on the exiting wall at required height from lower level for power connection, light connection and net working connection including partition chip flexible cover end cap. Make: Legrand .MK., or its equivalent as required complete in all respect.
	2		20	3	-	5
The same	309		444	7 7 10	9711	1407
TO STATE OF THE PARTY OF THE PA	Rupees three hundred nine only.		Rugges Four hundred forty four only.		Rupees Nine thousand seven hundred eleven only.	Rupees One thousand four hundred seven only.
	Each		MUR		Each	Meter
126298	819		8880		9711	14070

していたという

2758	Point	Rupees One thousand three hundred seventy nine only.	1379	2	Group C.	2.02
2758	Point	Rupees lone thousand three hundred seventy nine only.	1379	2	Group A.	2.01
					equivalent as approved by Engineer-in -charge,	
A STATE OF THE PARTY OF THE PAR				10-17	:-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its	1
The state of the s					suitable GI box and earthing the point with 1.5 sq.rum. FRLS PVC	The state of
0					Wiring for twin control light point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed heavy duty PVC conduit 2 way modular switch modular plate	2
	A CONTRACTOR OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN T	eighty seven only.	- V-	Sec.	一日の一日の一日の一大を全国の人口のは、人人	
29675	Point	Rupees One thousand one hundred	1187	25	Group C	1.02
1 11 1	A STATE OF	only.			日のからまればずれのことの	j
19362	Point	Rupees Nine hundred twenty two	922	21	Group A.	1.01
					Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed heavy duty pvc conduit, with modular switch, modular plate, suitable Gl box and earthing the pointwith 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.Make: Anchor (Roma classic), L&T(Entice), Legrand (Myrius) pvc conduit Diplast, AKG, BEC, POLY India or its equivalent as approved by Er-In-Charge	_
Amount	Omn	***************************************	-		prescribation of techno	No.
Amount	cin) Unit	stt. Hamirpur (HP) (SH:- Prov. E.I. then In lin words.	Rate In	Chail Ham	NAME OF WORK:- C/O Health Sub Centre with Residance at Dharog Tehail Hamirpur Distt. Hamirpur (HP) (SH:- Prov. E.l. therein) S. Description of Items Quantity Rate In In words.	S NEO
		Time Limit:- One year.				
		Earnest money:- Rs. 7,200/-				
	1	Estimated cost Rs. 3,57,781/-			The state of the s	
		91 '0k' 00r			DEAT SCHEDULE OF QUARTITY	ľ

	6.02	6.01	6		5	77.	3.02	3.01	
Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 6 pin 5/6 & 15/16, modular socket outlet and 15/16 amp&5 /6, connection etc. as required. Make :-Anchor (Roma classic),L&T(Entice),Legrand(Myrius) or its equivalent as approved by Er-In-Charge.	S/D3 X 4 sq. mm	SD3X1.5 sq. mm	Supplying and drawing following sizes of FRLS PVC insulated copper—conductor, single core cable in the existing surface/ recessed steel/ PVCconduit as required.	by Er-In-Charge.	Wiring for light/ power plug with 4X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed PVC conduit alongwith 1 No 4 sq.mm FRLS PVC insulated copper conductor single core cable for loop carthing as required.Make:-Plaza,KEI,Finolex or its equivalent as approved	Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed steel conduit alongwith 1 No 4 sq.mm FRLS PVC insulated copper conductor single core cable for loop earthing as required.Make:-Plaza,KEI,Finolex or its equivalent as approved by Er-In-Charge.	2 X 10 sq. mm + 1 X 6 sq. mm earth wire	2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed PVCconduit heavy as required. Maker-Plaza,KEI,Finolex & pvc conduit pipe AKG,BEC, Diplast-Poly india or its equivalent as approved by Er-In-Charge
L. V.	15	30			z	\$	13	95	
539	18	97			533	50 50	575	199	
Rupees Five hundred fifty nine only.	Rupees One hundred ninety only.	Rupees Ninety seven only.			Rupees Five hundred thirty three only.	Rupees three hundred eighteen only.	Rupees Five hundred seventy five only.	Rupees One hundred ninety nine only.	
Each	Meter				Meter	Meter	Meter	Meter	
7267	2850	2910	0		13325	14310	6900	18905	0

2884	Each	Rupees One thousand four hundred forty two only.	1442	1.0	Sapplying and fixing of fancy wall bracket of chrome finish colour with opal glass diffuser made of mild steel, with single holder containing thread type LED hump holder(s) of all sizes and shapes, complete with all accessories but excluding led lamp including making connections, testing etc. as required::MakeJaquar (Mode JNL-CHR-mb160275211A)), wipro, Philips or equivalent make	1
	Service Market				commissioning etc. Make: panasonic (Model - PBTM14267)/Philips_Jaquar or its equivalent as approved by Engineer-in-Charge (Five YEAR WARRANTY)	
2163	Each	Rupees Seven hundred twenty one only.	721	4	Sapplying and fixing Aluminium batter LED 26 wart, 6000k; and it should be compatible with specification i.e. Power Factor > 9. Harmonic Distortion 10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and	
8			j	Th.	and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make: PANASONIC(Model - PBLM15368MS)/Philips, Wipro or its equivalent as approved by Engineer-in-Charge	
44046	Each	Rupees Seven thousand three hundred forty one only.	7341	٥	Supplying and fixing SURFACE 1x4 36 WATT LED , 5700k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > 9. Harmonic Distortion<10%	10
910	Each	Rupees One hundred thirty only.	130	7	5 pin 5/6 amp socket outlet	9,02
532	Each	Rupees Seventy six only.	76	7	5/6 amp Modular switch	10.6
0			-		Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required	۰
				25-0	cover in front on surface or in recess, including providing and fixing 2 nos. 3 pin 5/6 amps modular socket outlets and 2 nos 5/6 amps modular switches, connection etc. as required. (For light plugs to be used in non residential buildings).	

18	17		16	5	r	5
Supplying and fixing PVC batten/ angle holder including connection etc. as required.	Supplying and fixing Ding-Dong / Electronic musical bell, suitable for D.C./A.C. single phase,230 volts complete as required:-	mounting 5700k, (Five YEAR WARRANTY) and it should be compatible with specification e.i. Power Factor > 9, Harmonic Distortion<10% and efficacy>100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make - Jaquar (Model -LSRT015060XW)/Philips/wipro or its equivalent as approved by Engineer-tn-Charge.	Supplying and fixing street light LED 60 watt with G.I bracket die cast. Aluminium housing with frame and toughened glass, pipe	Providing and installation of following type of LED retrofit Lamp B-22 holder base with polycarbomate diffusor and aluminium heat sink including connections, testing and commissioning etc. as required: Make JAQUAR, wipro Philips or its equivalent as approved by Engineer-in-Charge.	Supplying and fixing of bulk head fitting LED 12 watt ,6500k ,(Five YEAR WARRANTY) and it should be compatible with specification e.i. Power Factor > .9.Harmonic Distortion<10% and efficacy >100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.Make -Panasonic (CAT NO PBHM02127/WIPRO/PHILIPS, or its equivalent as approved by Engineer-in-Charge	supplying and fixing Aluminium batteri LED 10 wart, 6500k, and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion 10% and efficacy >100 Lumens per wart, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make: Jaquar (Model LGLZ01X010XC)/Philips,Panasonnic or its equivalent as approved by Engineer-in-Charge (Five YEAR WARRANTY)
4	2			6	4	
47	238		5573	139	59	
Rupees Forty seven only.	Rupees Two hundred thirty eight only.		Rupees Five thousand five hundred seventy three only.	Rupces One hundred thirty nine only.	Rupees One thousand eight hundred eighty one only.	rupees four numored (wenty only).
Each	Each		Each	Each	Each	DICE
188	476		22292	834	7524	1000

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1111111		
22	21	20	5
Supplying and fixing Aluminium batten-LED 26 wart, 6000k, and it should be compatible with specification Le Power Factor > 9, Harmonic Distortion<10% and efficacy >100 Lumens per wart, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make: panasonic (Model - PBTM14267)/Philips_Jaquar or its equivalent as approved by Engineer-in-Charge (Five YEAR WARRANTY)	Supplying and fixing of bulk head fitting LED 12 watt ,6500k ,(Five YEAR WARRANTY) and it should be compatible with specification c.i. Power Factor > .9,Harmonic Distortion<10% and efficacy >100 Lunners per watt, suitable for input voltage AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc.Make -Panasonic (CAT NO PBHM07127/WIPROPHILIPS, or its equivalent as approved by Engineer-in-Charge.	Supplying and fixing surface round type LED 12 wart, 6000k, (Five YEAR WARRANTY) and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion<10% and efficacy>100 Lumens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make:- Jaquarc (Model - LNRO02R0012SC)/Philips, wipro or its equivalent as approved by Engineer-in-Charge.	Supplying and fixing Aluminium butten LED 10 watt, 6500k, and it should be compatible with specification i.e. Power Factor > 9, Harmonic Distortion 10% and efficacy >100 Latmens per watt, suitable for input voltage: AC 220-240 V, 50/60Hz, complete with all accessories, connections, testing and commissioning etc. Make- Juquar (Model - LGLZ01X010XC)/Philips,Panasonnic or its equivalent as approved by Engineer-in-Charge (Five YEAR WARRANTY)
9			
721	<u> </u>	786	420
Rupees Seven hundred twenty one only.	Rupees One thousand eight hundred eighty one only.	Rupees Seven hundred eighty six only.	Rupees Four hundred swenty only,
Each	Each	Each	Each
6489	5643	3144	1680

PARTITION OF

Toward .		, 2		23	23.01	
	特。自然不同的	24.01	24	23.02		5
Browlding and installation of stationary storage type. Electric water heater (Geyser)of various sizes by means of expansion-bolts with nuts and washers, includingembedding of expansion-bolts in the wall, making good the damages, electrical connections, testing etc. complete as required. Make: - Usha (Model 10 L SWH MISTY WITH KIT), Bajaj, Recold or its equivalent as approved by Engineer-in-charge.	water heater (Geyser)of various sizes by means of expansion-bolts with nuts and washers, includingembedding of expansion-bolts in the wall, making good the damages, electrical connections, testing etc. complete as "required-Make." Usha (Model 25 L SWH MISTY WITH KIT), Bajaj Recold or its equivalent as approved by Engineer-in-charge.	Exhaust Fan, Light duty, (Domestic) 300 mm sweep Providing and installation of stationary storage type Electric	Providing and installation exhaust fan of following sizes in the existing opening including making the hole to suit the size of the above fan, making good thedamages, connections, testing and commissioning etc. as required: Make:- Usha,Bajaj,Crompton or its equivalent as approved by Engineer-in-charge(Five year warrafty)	900 mm	1200 mini	Providing, installation, testing and commissioning of cetting fan with socket type regulator, including wiring the down rods of standard length (up to 30 cm) with 160/20 minimin twisted flexible, cotton braided, copper cable, including providing and fixing phenolic laminated sheet cover on the fan box and earthing etc. as required. Make: Usha (TECHNIX PLUS 3 star), Bajaj, Crompton or its equivalent as approved by Er-incharge (warranty five year)
		J 20		**	6	
10182		2169		3097	3788	challe
Rapses. Ten thousand one hundred eighty two only.	hundred fifty seven only.	Rupees Two thousand one hundred sixty nine only. Rupees Twelve thousand two		Rupees Three thousand ninety seven only.	Rupees three thousand seven hundred eighty eight only.	
Each		Each		Each	Each	
20364		17352	0	3097	22728	

630	Meter	Rupees forty two only.	42	15	Providing and fixing 6 SWG (4 mm dia.) G.I. wire on surface or in recess for loop earthing as required.	u
3017	Each	Rupees Three thousand seventeen only.	3017		Double door-16 way act	32.02
2423	Each	Rupees Two thousand four hundred twenty three only.	2423	1	Double door-12 way	32.01
0					MCB distribution board, 240 volts, on surface' recess, complete with timed copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator	32
2390	Each	Rupees One thousand one hundred ninety five orfly.	5611	22	63 Amips	31.01
0					Supplying and fixing following rating, double pole, (single phase and neutral), 240 volts, residual current circuit breaker (RCCB), having a sensitivity current 30 milli amperes in the existing MCB DB complete with connections, testing and commissioning etc. as required. 63 AMP -	31
5260	Each	Rupees Two hundred sixty three only.	263	20	Supplying and fixing 5 umps to 32 amps rating, 240/415 volts, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.	30
2390	Each	Rupees One thousand one hundred ninety five only.	1195	2	Supplying and erection of 40/50/63 amps rating, 10 KA breaking capacity, 240 volts, 'C curves, miniature circuit breaker of following poles in the existing MCB DB complete with connections etc. as required:-	29
4800	Each	Rupees six hundred only.	600	se	Supply and fixing exhaust fan lower shutter for 300/380mm exhaust fan on the existing wall painting including 12 mm thick wooden ply board for suitable size of exhaust fan hole.	28
17352	Each	Rupees Two thousand one hundred sixty nine only.	2109		Providing and installation exhaust fan of following sizes in the existing opening, including making the hole to suit the size of the above fan, making good thedamages, connections, testing and commissioning etc. as required: Make:- Usha, Bajaj, Crompton or its equivalent as approved by Engineer-in-charge (Five year warranty)	

1	35	34
Total	Supplying and fixing true power make advanced earthing system having copper pipe 2 meter long 50 mm dia with terminal size 50x6 mm, internal strip size 25x3 with 25 Kg compound including exvation of pit and refiling the same and making earthing pit cover 13 inch dia as required complete in all respect, make: True power ,Earth plus,Ashloka or its equivalent as per best satisfaction of Engineer-in-charge.	Providing and laying earth connections from earth electrode with 6 SWG G.I. Wire in 15 mm dis. G.I. pipe from earth electrode etc. as required.
	-	10
	5082	287 Ruj ont
	Rupees Five thousand eighty two only.	Rupees Two hundred eighty seven only.
	Each	Meter
357781	5082	2870